	т п		0		A	٦
A	ØS Contraction of the second s					4
ω			LAYOUT SHOWN AS EX	AMPLE		3
	Keying Shown as example					
CHARACTERISTICS	Connector dimension	1				
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal	-				
-Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	ØS 41.7 Max Z' 31.5 Max VV THREAD M31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer			Country Jurisdiction & Control List			
► -Contact Plating : Gold over copper Alloy 0.8µm minimum			FR Not Listed			2
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D521M11AA			
-Temperature Range : -65°C to +200°C		A 07-10-20	016 First Release			_
-Salt Spray : 2000 hours						
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWIN	MOD N°	_
		TITLE	Composite Plug 8D series			
→ BASIC SERIES: 8D 5 - 21 M SHELL TYPE : Plug with RFI Shielding	M 11 A A	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact			SOURIAU This document is the property of SOURIAU. SOURIAU it must not be reproduced or			
SHELL SIZE : 21	CONTACT TYPE : PIN(5		communicated without			
	CONTACT LAY	OUT : 21-11	SOURIAU	DRG N°	SHEET	
PLATING : M = Nickel		A3	8D521M1		1/2	

r	<u>т</u>	۵	н г	m		0
		Contact Layout				
4	-x -	$ \begin{array}{c} $				
	B +306 (7.77) C +348 (8.84) D +227 (5.77) E +.000 (0.00) F -227 (5.77) Shell Arrangement size no.	Y-axis (mm) position ID X-axis (mm) Y-axis (mm) +.332 (8.43) G 348 (8.84) 061 (1.55) +.177 (4.50) H 306 (7.77) +.177 (4.50) 061 (1.55) J 121 (3.07) +.322 (8.43) 270 (6.86) K +.000 (0.00) +.123 (3.12) 353 (8.97) L +.000 (0.00) 115 (2.92) 270 (6.86) mber of ontacts Size Service Contact Supersedet	s			
ى ى	21 -11	11 12 I All MS20055-1	1			
						SOURIAU shall not be liable for a due to a use of the Products the Specifications issued by either (professional recommend
2						Cour Fl
						PN: 8D521
					A 07-10-20 ISS DATE	16 First Release Latest modification - by
					Designed By:	Date:
					TITLE	Comp
<u> </u>					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU
					FORMAT A3	SOURIA 8D521N
l	Н	G	F	E	D	C

