Characteristics Connector dimension - Standard : Based on MIL-DTL-38999 Series III Shell Material Aluminium Shell Plating Olive drab Cadmium Shell Plating Opper Alloy Souriacts Contacts Copper Alloy Seals & Grommet Silicon Elastomer Sourial Sourial In the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)	Γ	T Q T M	C	כ		0	σ		A	
Drawn Se EXAMPLE CHARACTERISTICS Sandwari: Based on MIL DTL:38999 Series III South Vintage Section III Status III Section III Status III Section IIII Section III Section III Section IIII Section IIIIIII Section IIII Section IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	4									4
CHARCTENSTCS Standard: Sased on MLL DT. 38999 Series III Shell Material :: Aluminium Shell Material :: Aluminium Shell Material :: Aluminium Shell Material :: Shell Sing :: Copper Alloy Scatart Plating :: Sold over copper Alloy 0.8µm minimum - Ourability :: Contact Plating :: Sold over copper Alloy 0.8µm minimum - Ourability :: Sold Mating cycles - Belivered without Souriau contacts - Mass :: Standard :: Sandard :: Sandard :: Sold Alloy 0.8µm minimum - Mass :: Standard :: Sold MRI Shielding - Mass :: Standard	ω					LAYOUT SHOWN AS E	XAMPLE			3
-Standard : Based on MIL DTL 38999 Series III -Standard : Based on MIL DTL 38999 Series III -Shell Material :: Aluminium -Shell Material :: Contacts -Contacts :: Coper Alloy -Seals & Grommet :: Silicon Bastomer -Contact Nation :: Sold over coper Alloy 0.8µm minimum -Durability :: Sold over coper Alloy 0.8µm minimum -Delevered without Souriau contacts PN: 8D521W41PCL -Mass :: 37.07 g :: 10% -Mass :: 37.07 g :: 10% Stell TYPE : Souriau Mills Relians Stell TYPE : Subard Crimp Contact Stell TYPE : Sandard Crimp Contact		Keying Shown as example								
-Standard: Based on MIL-DTL 38899 Series III Dim Nominal Standard: Based on MIL-DTL 38899 Series III -Shell Material :: Aluminium -Shell Nature SOURIAU shall not be flable for any non-conformity or damage -Shell Pating :: Opper Alloy -Standard: Based on MIL-DTL 38899 Series SOURIAU shall not be flable for any non-conformity or damage -Shell Pating :: Opper Alloy -Said & Grommer :: Silicon Elastomer -Contact Pating :: Sold over copper Alloy 0.8µm minimum - -Durability :: Sold over copper Alloy 0.8µm minimum - -Durability :: Sold over copper Alloy 0.8µm minimum - -Durability :: Sold over copper Alloy 0.8µm minimum - -Durability :: Sold over copper Alloy 0.8µm minimum - -Durability :: Sold over copper Alloy 0.8µm minimum - -Durability :: Sold over copper Alloy 0.8µm minimum - -Durability :: Sold over copper Alloy 0.8µm minimum - -Mass :: 37.07 g ± 10% - 21 Mass : 10-10-2016 First Release - Solutity Contract type: : INstanded Crimp Contact Sotit -		CHARACTERISTICS Connector dimension								
Shell Mattali ∴ Autimutum Shell Mattali ∴ Contact Plating ∴ Contact Plating SolutiAut January ∴ SolutiAut January ∑ attaliant the Specification susued by either of the Parties or by a third party (professional recommendation, technical notice.) SolutiAut January ∴ Contact Plating ∴ SolutiAut January ∑ attaliant the Specification susued by either of the Parties or by a third party (professional recommendation, technical notice.) SolutiAut January ∴ SolutiAut January ∑ attaliant the Specification susued by either of the Parties or by a third party (professional recommendation, technical notice.) SolutiAut January ∴ SolutiAut January ∑ attaliant the Specification susued by either of the Parties or by a third party (professional recommendation, technical notice.) - Delivered without Souriau Contact - Delivered without Souriau Contact Physical Automendation technical notice.) - Mass : 37.07 g ± 10% Attaliant the Specification -		-Standard : Based on MIL-DTL-38999 Series III Dim Nominal								
N -Contact Plating ::: Gold over copper Alloy 0.8µm minimum -Durability ::: 500 Mating cycles -Delivered without Souriau contacts -Temperature Range ::: 65°C to ±175°C -Sait Spray ::: 500 hours -Mass ::: 37.07 g ± 10% -Mol Listed BASIC SERIES:::: 8D 5 - 21 W 41 P C L Delivered W/O Contact: - 000 memory - 000 memory - 000 memory SHELL TYPE :: Plug with RFI Shielding - 21 W 41 P C L CONTACT TYPE :: Standard Crimp Contact - 21 W 41 P C L SHELL TYPE :: Plug with RFI Shielding - 21 W 41 P C L CONTACT TYPE :: Standard Crimp Contact - 21 W 41 P C L SHELL TYPE :: Plug with RFI Shielding - 21 W 41 P C L CONTACT TYPE :: Standard Crimp Contact - 21 W 41 P CONTACT TYPE : Pln(500 Matings) - 000 P RHLL SIZE : 21 - 01/2 C W rab Cadmium CONTACT LAYOUT : 21-41 - 01/2 C W rab Cadmium - 01/2 C W rab Cadmium - 01/2 W WW.SOURIAU.COM - 11/2 Mount is the property of com		-Shell Material Z 31 Max -Shell Plating : Olive drab Cadmium VV THREAD M31x1-6g -Insulator : Thermoplastic			due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party					
-Durability : 500 Mating cycles -Delivered without Souriau contacts -Temperature Range : 65°C to +175°C -Sait Spray : 500 hours -Mass : 37.07 g ± 10% BASIC SERIES: 80 5 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Staddard Crimp Contact SHELL SZE : 21 PLATING : W = Olive drab Cadmium	N						ry Jurisd			2
-Salt Spray : 500 hours -Mass : 37.07 g ± 10% BASIC SERIES: 8D 5 - 21 W 41 P C L SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21 PLATING : W = Olive drab Cadmium CONTACT TYPE : Dive drab Cadmium CONTACT TYPE : Plug with are produced or communicated without permission CONTACT TYPE : Olive drab Cadmium CONTACT TYPE : Plug with are a communicated without permission CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21 PLATING : W = Olive drab Cadmium SOURIAU CONTACT TYPE : Plug with are a communicated without permission CONTACT TYPE : Plug with are a communicated without pe		-Durability : 500 Mating cycles							2	
-Salt Spray : 500 hours -Mass : 37.07 g ± 10% -Mass : 37.07 g ± 10% BASIC SERIES: 8D 5 2 21 W 41 P C L SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21 PLATING : W = Olive drab Cadmium CONTACT TYPE : PIN(500 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : PIN(500 Matings) CONTACT TYPE : PIN(500 Matin				A 10	0-10-2016	First Release				
Mile Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D 5 - 21 W 41 P C L BASIC SERIES: 8D 5 - 21 W 41 P C L SHELL TYPE : Plug with RFI Shielding										
BASIC SERIES: 8D 5 - 21 W 41 P C L BASIC SERIES: 8D 5 - 21 W 41 P C L SHELL TYPE : Plug with RFI Shielding Delivered W/O Contact ORIENTATION : C SCALE M General linear NPRDS / PROJECT CONTACT TYPE : Standard Crimp Contact ORIENTATION : C ORIENTATION : C SOURIAU This document is the property of sOURIAU SHELL SIZE : 21 ONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 21-41 FORMAT SOURIAU DRG N° SHEET		-Mass : 37.07 g ± 10%						CUSTOMER DRAV		
AND SERVES. BASIC SERVES. BASIC SERVES. BASIC SERVES. Tolerances: Tolerances: BS9 SHELL TYPE : Plug with RFI Shielding ORIENTATION : C ORIENTATION : C NA SOURIAU This document is the property of SOURIAU.COM SHELL SIZE : 21 CONTACT TYPE : Plug with RFI Shielding CONTACT TYPE : PIN(500 Matings) CONTACT TYPE : PIN(500 Matings) This document is the property of SOURIAU.COM SOURIAU PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21-41 FORMAT SOURIAU DRG N° SHEET				TI	TLE	Alumir	nium Plug 8	D series		
CONTACT TYPE : Standard Crimp Contact ORIENTATION : C SHELL SIZE : 21 CONTACT TYPE : PIN(500 Matings) PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21-41	_		itacts						СТ	
SHELL SIZE : 21 CONTACT TYPE : PIN(500 Matings) communicated without permission PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21-41 FORMAT SOURIAU DRG N° SHEET		CONTACT TYPE : Standard Crimp Contact ORIENTATIO	DN : C		RIAU		COM	SOUI it must not be	RIAU reproduced or	
			— L							
A3 8D521W41PCL-C 1/2		PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 2	21-41							
H G F E C B A	L								1/2	

r	Т	۵	וד	m	U	0
		Contact Layout				
4		+Y				
	<	31° 23 31° 23 10° 20 HOLES 10° 20 HOLES				
_						
			7			
ယ	size no. con	Insert arrangement 21-41 ber of Size Service Contact Supersedes tacts contacts rating location H1 20 I All MS20055-41	-			
	\vdash					SOURIAU shall not be liable for ar
						due to a use of the Products w the Specifications issued by either o
						(professional recommenda
N						Count FR
						PN: 8D521V
						116 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
					SCALE	General linear Tolerances:
<u> </u>						
					SOURIA	
					FORMAT A3	SOURIAU 8D521W
l	Н	G	F	E	D	C

σ		Þ					
				4			
				3			
any non-conformit which does not co							
r of the Parties or b dation, technical n	by a third party						
ntry Jurisd	liction & Contro	ol List					
R	Not Listed			2			
W41PCL							
				-			
			MOD N°				
	CUSTOMER	DRAWING		-			
inium Plug 8D series							
r	NPRDS / P						
	859 This docu	9 ment is the prop	erty of	1			
.COM	SOURIAU it must not be reproduced or communicated without permission						
U DRG N°	communica		SHEET				
V41PCL-C			2/2				
В		А		1			