ב	т п		0	₿ ♪	
ØS~					
			LAYOUT SHOWN AS EXAM	APLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension				
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal				
-Shell Material : Aluminium -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy				does not comply with e Parties or by a third party	
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List	
-Contact Plating : Gold over copper Alloy 0.8μm minimum			FR	Not Listed	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D525F6	1BB	
-Temperature Range : -65°C to +200°C		A 06-10-2016	; First Release		
-Salt Spray : 48 hours					
		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
		TITLE	Aluminiu	m Plug 8D series	
BASIC SERIES: 8D 5 - 25 F	61 B B	SCALE	General linear	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding		NA .	Tolerances:	859	
CONTACT TYPE : Standard Crimp Contact	ORIEN			This document is the pro- SOURIAU	operty of
SHELL SIZE : 25	CONTACT TYPE : SOCKET(50	SUURIAU	WWW.SOURIAU.CO	M it must not be reprodu communicated without p	
PLATING : F = Nickel	CONTACT TIPE : SOCKET(SO		SOURIAU D		SHEET
	CONTACT LATC	A3	8D525F61		1/2
					1/2

