	E G	г	m	D	0	B			
4	R 22.6 Max () () () () () () () () () () () () ()	N Thread	S		<image/> <section-header></section-header>	AMPLE		4	
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Keying Shown a	Connector dimension Dim Nominal						
2	-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm	n minimum	A34.9±0.3B19.07+0.1/-0.15R32.5MaxS31.8±0.4W2.2+0.9/-0.1VV THREADM15x1-6g		SOURIAU shall not be liable for any i due to a use of the Products whic the Specifications issued by either of t (professional recommendatio Country FR	ch does not comply with he Parties or by a third party on, technical notice.)		2	
	<ul> <li>-Durability : 500 Mating cycles</li> <li>-Delivered with Souriau contacts and Accessories</li> <li>-Temperature Range : -65°C to +200°C</li> <li>-Salt Spray : 48 hours</li> </ul>			A 30-09-2016	PN: 8D711F	99SD		_	
	-Mass : 21.28 g ± 10%			ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°		
				TITLE	Aluminium	Receptacle 8D series	cle 8D series		
-	BASIC SERIES:8D7-SHELL TYPE: Jam nut Receptacle	11 F 99 S D		SCALE -{	General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the pro	perty of	- _ 1	
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11		ORIENTATION :   CONTACT TYPE : SOCKET(500 Matings	- SUURIAU	WWW.SOURIAU.CO	COUDIALI	ced or		
	PLATING : F = Nickel		CONTACT LAYOUT : 11-9	FORMAT A3	SOURIAU I 8D711F9		SHEET		
L	H G	F	E	D	C	B A		J	

F	D I	ш		
4	Contact Layout $f \\ f \\$		Panel cutout JAM NUT RECEPTACLE (TYPE 7)	4
	Contacts (Insert arrangement 11-99)           Contact position ID         Location X-axis         Y-axis (mm)           A         +.065 (1.65)         +.113 (2.87)           B         +.130 (3.30)         +.000 (0.00)         C         +.065 (1.65)         +.113 (2.87)         D        065 (1.65)        113 (2.87)         D        065 (1.65)        113 (2.87)         E        130 (3.30)         +.000 (0.00)         F        065 (1.65)         +.113 (2.87)         G         +.000 (0.00)         <			
ى ت	size     no.     contacts     contacts     rating     location       11     -99     7     20     I     All     MS20050-99		Dim         Nominal           B         19.59+0/-0.25           ØC         20.96+0.25/-0	3
			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)	
N			Country       Jurisdiction & Control List         FR       Not Listed         PN: 8D711F99SD         A       30-09-2016         First Release       First Release	2
			ISS     DATE     Latest modification - by     MOD N°       Designed By:     Date:     CUSTOMER DRAWING       TITLE     Aluminium Receptacle 8D series	_
<u> </u>			SCALE       Image: SCALE       General linear       NPRDS / PROJECT         NA       Image: Tolerances:       #       859         SOURIAU       WWW.SOURIAU.COM       This document is the property of SOURIAU         FORMAT       SOURIAU DRG N°       SHEET	1
	H G	F F	A3 8D711F99SD-C 2/2 D C B A	