

| _ | D I | нт — | m | | | 0 | | | | _ | |
|---|--|--|--|--|--------------------------------------|---|--|---|--------|---|--|
| 4 | | ter de la construction de la con | | | | | | | | | |
| N | CHARACTERISTICS -Standard : Based on ML-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minin -Durability : 500 Mating cycles -Delivered without Souriau contacts | | ExampleConnector dimensionDimNominalA44.5±0.3B30.15+0.1/-0.15R32.5MaxS41.3±0.4W2.2+0.9/-0.1VV THREADM25x1-6g | | | due to a use of the Pro the Specifications issued by (professional reco | | ly with third party | | 2 | |
| | -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 41.7 g ± 10% BASIC SERIES: 8D 7 - 17 SHELL TYPE : Jam nut Receptacle | W 75 S B L | Delivered W/ | | ISS DATE Designed By: TITLE SCALE NA | Gener Toler | minium Receptacle | NPRDS / PROJECT 859 This document is the prop | MOD N° | 1 | |
| | CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 PLATING : W = Olive drab Cadmium H G | F | ORIEN CONTACT TYPE : SOCKET(50 CONTACT LAYO | | SOURIAU FORMAT A3 | SOU | RIAU.COM RIAU DRG N° 17W75SBL-C B | SOURIAU it must not be reproduc communicated without pe | | | |

| Г | т | ۵ | | П | | m | D | 0 | | Þ | | - | |
|----------|---------------|----------------|--------------------|---|--|---|---|---|---------------------------------|---|--------|---|--|
| | | Contact Layout | | | | | | Panel cutout | | | | | |
| | 75 | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | | |
| | Ctc A B | | Y 4.75 -4.75 | | | | | ØC | | | | | |
| ω | | | | | | | | Dim Noming B 30.73+0/ ØC 32.01+0. | /-0.25 | | | 3 | |
| | _ | | | | | | | SOURIAU shall not be l | liable for any non-conformit | y or damage | | | |
| | | | | | | | due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) | | | | | | |
| N | | | | | | | | | Country Jurisd FR | iction & Control List Not Listed | | 2 | |
| | | | | | | | PN: 8D717W75SBL | | | | | | |
| | | | | | | | A 01-10-20 | 16 First Release | | | | | |
| | | | | | | | ISS DATE Designed By: | Latest modification - by Date: | | CUSTOMER DRAWING | MOD N° | | |
| | | | | | | | TITLE | Al | uminium Receptacl | e 8D series | | | |
| <u> </u> | | | | | | | SCALE NA | | neral linear blerances: ± | NPRDS / PROJECT 859 | | - | |
| | | | | | | | SOURIA | U WWW.SOL | JRIAU.COM | This document is the prop SOURIAU it must not be reproduc communicated without per | ed or | | |
| | | | | | | | FORMAT A3 | | URIAU DRG N° | | SHEET | - | |
| | | | | | | | | 8D | 717W75SBL-C | | 2/2 | | |