
93

Made of high quality steel wire which combines strength with superior forming. The units offer clean, strong butt welds with minimum flash and have consistent guard diameters to enhance maximum air-flow and

- · Available for most popular size fans
- · Protects fingers as well as fan blades
- · Same mounting hole pattern as standard fans
- · Chrome Plate offers a high luster finish

MATERIAL: Steel, Nickel Chrome Plate

## FITS 1.50" (40mm) FANS




#### CONSTRUCTION

CAT. NO. 8447

Rings: .063 (1.60) wire diameter Ribs: .063 (1.60) wire diameter


## FITS 2.50" (60mm) FANS



## CONSTRUCTION

Rings: .063 (1.60) wire diameter Ribs: .063 (1.60) wire diameter

## FITS 3.12" (80mm) FANS




## CONSTRUCTION

CAT. NO. 8450

CAT. NO. 8452

Rings: .063 (1.60) wire diameter **Ribs:** .063 (1.60) wire diameter

## FITS 3.62" (92mm) FANS



CAT. NO. 8451


Rings: .063 (1.60) wire diameter **Ribs:** .063 (1.60) wire diameter

## FITS 4.50" (120mm) FANS

CAT. NO. 8449

CAT. NO. 8448


CAT. NO. 8455



### CONSTRUCTION

Rings: .063 (1.60) wire diameter Ribs: .063 (1.60) wire diameter


## FITS 4.50" (120mm) FANS



### CONSTRUCTION

Rings: .071 (1.80) wire diameter Ribs: .091 (2.31) wire diameter


## FITS 4.50" (120mm) FANS



## CONSTRUCTION

Rings: .071 (1.80) wire diameter CAT. NO. 8453 Ribs: .071 (1.80) wire diameter


## FITS 6.00" (150mm) FANS



## CONSTRUCTION

Rings: .071 (1.80) wire diameter **Ribs:** .091 (2.31) wire diameter

## FITS 10.00" (250mm) FANS



## CONSTRUCTION

Rings: .091 (2.31) wire diameter CAT. NO. 8457 **Ribs:** .091 (2.31) wire diameter

# <u>KEYSTONE</u>

## Tel (718) 956-8900 • Fax (718) 956-9040 (800) 221-5510 • kec@keyelco.com