

KEMET, QMS, SMD Motion Detection with Fresnel Lens Evaluation Kit, Infrared, I²C Communication Compatible, Small SMD Package, High Dynamic Range



| Packaging Specifications | | |
|--------------------------|---------------|--|
| Packaging: | Cardboard Box | |
| Packaging Quantity: | 1 | |
| Weight: | 300 g | |

| General Information | |
|---------------------|---|
| Series: | QMS |
| Туре: | Motion Detection |
| Style: | Connector |
| Description: | Evaluation Kit |
| Kit Contains: | USEQMS motion sensor kit, sensor USEQMSEA011680, USB communications cable |
| REACH | SVHC (PZT - CAS 12626-81-2) |
| SCIP Number | 4bbe8810-62a4-426f-9a2e-98d9d0d9acfe |
| Qualifications | REACH |
| RoHS: | With Exemptions |

| Specifications | |
|-----------------------|---|
| Temperature Range: | -40/+85°C |
| Miscellaneous: | SMD motion detection with fresnel lens evaluation kit, including 1 QMS sensor |
| Power Supply Voltage: | 1.75 – 3.6 V |
| Current: | 1 – 23 μA (Supply Current Typical) |
| D*: | 2.5 x 10 ⁸ cm sqrt (Hz)/W |
| NEP: | 2.7 x 10 ⁻¹⁰ W/sqrt (Hz) |
| Time Constant: | 10 ms (10 – 20 Hz peak) |
| Field of View: | 90 degrees |
| Element Size: | 0.410 mm² (1 pixel) |
| Filter Aperture: | d = 1.65 mm |

For additional sources of information, please refer to https://www.kemet.com/en/us/sensors/environmental-sensors.html