

BARBARA

Ø70 mm LEDiL System Reflectors compatible with various accessories, sockets and solderless connectors and up to 19 mm LES size COBs

BARBARA family consists of three subfamilies for midsized COBs. The newest addition to the family - BARBARA-G2 is compatible with LEDiL HEKLA due to a bayonet fastening mechanism. Product size is optimized to offer beam angles (FWHM) from a very narrow 13° to a wide 75° flood. LEDiL's RZ-sublens allows BARBARA to be used in applications from retail to stage lighting with full RGBW and tunable white colour mixing.


BARBARA-G2

Variant compatible with LEDiL HEKLA connectors/sockets




PRODUCTS:

F16366_BARBARA-G2-WW




Dimensions: 70.0 mm x 70.0 mm
Height: 41.90 mm
~60° wide beam compatible with LEDiL HEKLA

F16365_BARBARA-G2-W



Dimensions: 70.0 mm x 70.0 mm
Height: 41.90 mm
~40° wide beam compatible with LEDiL HEKLA


F16364_BARBARA-G2-M



Dimensions: 70.0 mm x 70.0 mm
Height: 41.90 mm
~25° wide beam compatible with LEDiL HEKLA

PRODUCTS:

F16363_BARBARA-G2-S



Dimensions: 70.0 mm x 70.0 mm

Height: 41.90 mm

~12° spot beam compatible with LEDiL

HEKLA

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)