


DAISY

Solutions for premium class indoor lighting. Part of LEDiL's Dark Light concept with UGR <19. Optimized for 2835 and compatible with up to 5630 size mid-power LED packages.

DAISY is a perfect solution for premium class indoor lighting with a seamless glare eliminating shade and highly efficient lenses. Available in 28X1, 4X1, 7X1, 8X1, 2X2 and MINI form factors in black or white with gloss or matt finish. Can be adapted to many types of recessed, surface mounted or pendant luminaire designs.


DAISY-28X1

1140 x 40 mm linear solution with 28X1 shade



PRODUCTS:

DAISY-28X1-W2-B




Dimensions: 1140.0 mm x 40.0 mm

Height: 20.20 mm

Variant with 7X1 lenses.

~50° wide beam with tighter cutoff.


DAISY-28X1-W-B



Dimensions: 1140.0 mm x 40.0 mm Height: 20.20 mm

~50° wide beam. Variant with 7X1 lenses.

DAISY-28X1-WW-B




Dimensions: 1140.0 mm x 40.0 mm Height: 20.20 mm

~80° wide beam. Variant with 7X1 lenses.



PRODUCTS:


DAISY-28X1-W-D



Dimensions: 1140.0 mm x 40.0 mm Height: 20.20 mm

~50° wide beam. Variant with diffused 4X1 lenses.


DAISY-28X1-WW-D



Dimensions: 1140.0 mm x 40.0 mm Height: 20.20 mm

~80° wide beam. Variant with diffused 4X1 lenses.

DAISY-28X1-W




Dimensions: 1140.0 mm x 40.0 mm

Height: 20.20 mm

~50° wide beam. Variant with 4X1 lenses.

DAISY-28X1-WW




Dimensions: 1140.0 mm x 40.0 mm

Height: 20.20 mm

~80° wide beam. Variant with 4X1 lenses.

DAISY-28X1-W2-B-D




Dimensions: 1140.0 mm x 40.0 mm

Height: 20.20 mm

~50° wide beam with tighter cutoff. Variant with diffused 7X1 lenses.

DAISY-28X1-W-B-D



Dimensions: 1140.0 mm x 40.0 mm


Height: 20.20 mm

~50° wide beam. Variant with diffused 7X1 lenses.



PRODUCTS:

DAISY-28X1-WW-B-D



Dimensions: 1140.0 mm x 40.0 mm

Height: 20.20 mm

~80° wide beam. Variant with diffused

7X1 lenses.



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy