

EMILY-RS

~8° spot beam. 14.74 mm high lens.

SPECIFICATION:

Dimensions	Ø 26.0 mm
Height	14.7 mm
Fastening	tape
ROHS compliant	yes ⓘ

MATERIALS:

Component	Type	Material	Colour	Finish
EMILY-RS	Single lens	PMMA	clear	
SPUTNIK-TAPE	Tape	Acrylic foam	black	











ORDERING INFORMATION:

Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CA13546_EMILY-RS » Box size: 480 x 280 x 300 mm	Single lens	1690	260	130	10.3











See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):

<p>CREE → LED</p> <p>LED XB-H FWHM / FWTM 9.0° / 17.0° Efficiency 88 % Peak intensity 24.7 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>CREE → LED</p> <p>LED XP-G3 FWHM / FWTM 10.0° / 18.0° Efficiency 94 % Peak intensity 18 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>CREE → LED</p> <p>LED XP-L HD FWHM / FWTM 13.0° / 23.0° Efficiency 89 % Peak intensity 13.1 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>CREE → LED</p> <p>LED XP-L HI FWHM / FWTM 8.0° / 15.0° Efficiency 88 % Peak intensity 28 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		

OPTICAL RESULTS (MEASURED):

<p>CREE → LED</p> <p>LED: XP-L2 FWHM / FWTM: 13.0° / 25.0° Efficiency: 93 % Peak intensity: 10 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>		
<p>CREE → LED</p> <p>LED: XQ-E HI FWHM / FWTM: 4.0° / 9.0° Efficiency: 94 % Peak intensity: 71.1 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>		
<p>CREE → LED</p> <p>LED: XT-E FWHM / FWTM: 8.0° / 16.0° Efficiency: 91 % Peak intensity: 23.9 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>		
<p>LUMILEDS</p> <p>LED: LUXEON Z ES FWHM / FWTM: 5.0° / 11.0° Efficiency: 91 % Peak intensity: 52 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>		

OPTICAL RESULTS (MEASURED):

NICHIA

LED	NVSW219D
FWHM / FWTM	10.0° / 18.0°
Efficiency	94 %
Peak intensity	20.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




NICHIA

LED	NVSW719AC
Assembly	NULL
FWHM / FWTM	9.0° / 15.0°
Efficiency	95 %
Peak intensity	28.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	










OSRAM
Opto Semiconductors

LED	OSLON Square EC
FWHM / FWTM	8.0° / 15.0°
Efficiency	90 %
Peak intensity	29.1 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

OSRAM
Opto Semiconductors

LED	PLPVEC2 850A
FWHM / FWTM	4.0° / 11.0°
Efficiency	%
LEDs/each optic	1
Light colour	IR
Required components:	

OPTICAL RESULTS (MEASURED):

<p> SEIOUL SEMICONDUCTOR</p> <p>LED nPola</p> <p>FWHM / FWTM 5.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 81.2 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p> SEIOUL SEMICONDUCTOR</p> <p>LED Z5M1/Z5M2</p> <p>FWHM / FWTM 9.0° / 15.0°</p> <p>Efficiency 91 %</p> <p>Peak intensity 23.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		

OPTICAL RESULTS (SIMULATED):

<p>CREE → LED</p> <p>LED: XHP35 HI FWHM / FWTM: 10.0° / 18.0° Efficiency: 96 % Peak intensity: 22 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>CREE → LED</p> <p>LED: XP-E2 FWHM / FWTM: 6.0° / 14.0° Efficiency: 94 % Peak intensity: 51.8 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>CREE → LED</p> <p>LED: XP-G2 FWHM / FWTM: 8.0° / 16.0° Efficiency: 94 % Peak intensity: 30.4 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>CREE → LED</p> <p>LED: XP-G2 HE FWHM / FWTM: 10.0° / 20.0° Efficiency: 95 % Peak intensity: 19.1 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	


OPTICAL RESULTS (SIMULATED):

<p>CREE LED</p> <p>LED: XP-P FWHM / FWTM: 6.0° / 12.0° Efficiency: 96 % Peak intensity: 63.8 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>LUMILEDS</p> <p>LED: LUXEON C FWHM / FWTM: 7.0° / 16.0° Efficiency: 94 % Peak intensity: 37.3 cd/lm LEDs/each optic: 1 Light colour: Royal Blue Required components:</p>	
<p>LUMILEDS</p> <p>LED: LUXEON HL2Z FWHM / FWTM: 8.0° / 18.0° Efficiency: 96 % Peak intensity: 27.7 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>LUMILEDS</p> <p>LED: LUXEON MZ FWHM / FWTM: 14.0° / 26.0° Efficiency: 95 % Peak intensity: 10.7 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	

OPTICAL RESULTS (SIMULATED):


LUMILEDS

LED LUXEON Rebel
 FWHM / FWTM 6.0° / 14.0°
 Efficiency 94 %
 Peak intensity 41.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LUMILEDS

LED LUXEON Rebel Plus
 FWHM / FWTM 6.0° / 14.0°
 Efficiency 94 %
 Peak intensity 42.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LUMILEDS

LED LUXEON Rubix
 FWHM / FWTM 6.0° / 12.0°
 Efficiency 96 %
 Peak intensity 63.9 cd/lm
 LEDs/each optic 1
 Light colour Blue
 Required components:



LUMILEDS





LED LUXEON Rubix
 FWHM / FWTM 6.0° / 12.0°
 Efficiency 96 %
 Peak intensity 64.5 cd/lm
 LEDs/each optic 1
 Light colour Green
 Required components:







OPTICAL RESULTS (SIMULATED):

<p>LUMILEDS</p> <p>LED: LUXEON Rubix</p> <p>FWHM / FWTM: 6.0° / 12.0°</p> <p>Efficiency: 96 %</p> <p>Peak intensity: 62.6 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p>LUMILEDS</p> <p>LED: LUXEON Rubix</p> <p>FWHM / FWTM: 6.0° / 12.0°</p> <p>Efficiency: 96 %</p> <p>Peak intensity: 67.4 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: Red</p> <p>Required components:</p>	
<p>LUMILEDS</p> <p>LED: LUXEON Z</p> <p>FWHM / FWTM: 5.9° / 12.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 65.3 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p>NICHIA</p> <p>LED: NCSxE17A</p> <p>FWHM / FWTM: 6.0° / 16.0°</p> <p>Efficiency: 93 %</p> <p>Peak intensity: 35.5 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	

OPTICAL RESULTS (SIMULATED):

<p>NICHIA</p> <p>LED: NCSxE17A FWHM / FWTM: 8.0° / 16.0° Efficiency: 92 % Peak intensity: 32.5 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>NICHIA</p> <p>LED: NVSW3x9A FWHM / FWTM: 12.0° / 22.0° Efficiency: 95 % Peak intensity: 16.3 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>NICHIA</p> <p>LED: NVSxE21A FWHM / FWTM: 8.0° / 18.0° Efficiency: 94 % Peak intensity: 27.8 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>NICHIA</p> <p>LED: NVSxE21A FWHM / FWTM: 8.0° / 18.0° Efficiency: 93 % Peak intensity: 26.2 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	





OPTICAL RESULTS (SIMULATED):

<p>NICHIA</p> <p>LED NVSxx19B/NVSxx19C FWHM / FWTM 10.0° / 18.0° Efficiency 95 % Peak intensity 22.4 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED Duris S5 (Single chip) FWHM / FWTM 9.0° / 18.0° Efficiency 89 % Peak intensity 23.2 cd/lm LEDs/each optic 1 Light colour Purple Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED Duris S5 (Single chip) FWHM / FWTM 8.0° / 18.0° Efficiency 96 % Peak intensity 25.4 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSCONIQ C 2424 FWHM / FWTM 8.0° / 16.0° Efficiency 96 % Peak intensity 36.2 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	







OPTICAL RESULTS (SIMULATED):

<p>OSRAM Opto Semiconductors</p> <p>LED OSCONIQ P 3030</p> <p>FWHM / FWTM 10.0° / 20.0°</p> <p>Efficiency 96 %</p> <p>Peak intensity 20.8 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOK Black</p> <p>FWHM / FWTM 11.0° / 20.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 19.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOK Black Flat</p> <p>FWHM / FWTM 6.3° / 14.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 50.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOK PURE 1010</p> <p>FWHM / FWTM 8.0° / 16.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 29.8 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	

OPTICAL RESULTS (SIMULATED):

<p>OSRAM Opto Semiconductors</p> <p>LED OSLOM Square CSSRM2/CSSRM3</p> <p>FWHM / FWTM 11.0° / 21.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 19.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOM SSL 120</p> <p>FWHM / FWTM 7.0° / 14.0°</p> <p>Efficiency 96 %</p> <p>Peak intensity 45.5 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour Amber</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOM SSL 150</p> <p>FWHM / FWTM 7.0° / 14.0°</p> <p>Efficiency 96 %</p> <p>Peak intensity 44.5 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour Amber</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOM SSL 150</p> <p>FWHM / FWTM 6.0° / 14.0°</p> <p>Efficiency 96 %</p> <p>Peak intensity 47.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	


OPTICAL RESULTS (SIMULATED):

<p>OSRAM Opto Semiconductors</p> <p>LED: OSLOM SSL 80</p> <p>FWHM / FWTM: 7.0° / 14.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 38 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED: SFH 4170S</p> <p>FWHM / FWTM: 6.0° / 11.0°</p> <p>Efficiency: 87 %</p> <p>LEDs/each optic: 1</p> <p>Light colour: IR</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED: SFH 4716AS</p> <p>FWHM / FWTM: 8.0° / 14.0°</p> <p>Efficiency: 96 %</p> <p>LEDs/each optic: 1</p> <p>Light colour: IR</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED: SFH 4725AS</p> <p>FWHM / FWTM: 8.0° / 18.0°</p> <p>Efficiency: 95 %</p> <p>LEDs/each optic: 1</p> <p>Light colour: IR</p> <p>Required components:</p>	<div style="display: flex; align-items: center;">    </div>

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED	LM301B
FWHM / FWTM	9.0° / 18.0°
Efficiency	94 %
Peak intensity	28.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)