

GABRIELLA-MIDI-S

~10° spot beam with holder and installation tape

SPECIFICATION:

Dimensions	Ø 37.8 mm
Height	24.1 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ



MATERIALS:



Component	Type	Material	Colour	Finish
GABRIELLA-MIDI-S	Single lens	PMMA	clear	
GABRIELLA-MIDI-HLD	Holder	PC	black	
GABRIELLA-MIDI-TAPE	Tape	Acrylic foam	black	



ORDERING INFORMATION:

Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CA16202_GABRIELLA-MIDI-S	Single lens	500	100	50	11.7
» Box size: 476 x 273 x 292 mm					







See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):



CREE LED

LED XHP35 HI
 FWHM / FWTM 10.0° / 19.0°
 Efficiency 90 %
 Peak intensity 20.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





CREE LED

LED XHP50.2
 FWHM / FWTM 15.0° / 28.0°
 Efficiency 87 %
 Peak intensity 9.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





CREE LED

LED XM-L RGBW (XMLDCL HI)
 FWHM / FWTM 11.0° / 20.0°
 Efficiency 89 %
 Peak intensity 17 cd/lm
 LEDs/each optic 1
 Light colour RGBW
 Required components:



LUMILEDS



LED LUXEON 5050 Round LES
 FWHM / FWTM 14.0° / 26.0°
 Efficiency 91 %
 Peak intensity 12.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):


LUMILEDS

LED LUXEON C
 FWHM / FWTM 17.0° / 28.0°
 Efficiency 85 %
 Peak intensity 8.2 cd/lm
 LEDs/each optic 1
 Light colour RGBW
 Required components:





LUMILEDS

LED LUXEON CZ
 FWHM / FWTM 16.0° / 26.0°
 Efficiency 89 %
 Peak intensity 9.3 cd/lm
 LEDs/each optic 4
 Light colour RGBW
 Required components:




LUMILEDS

LED LUXEON V
 FWHM / FWTM 11.0° / 22.0°
 Efficiency 89 %
 Peak intensity 15.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LUMINUS



LED SBM-40-RGBW
 FWHM / FWTM 10.0° / 19.0°
 Efficiency 89 %
 Peak intensity 21.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





OPTICAL RESULTS (MEASURED):





LED NCSxE17A
 FWHM / FWTM 13.0° / 26.0°
 Efficiency 92 %
 Peak intensity 11.6 cd/lm
 LEDs/each optic 4
 Light colour RGBW
 Required components:




LED NVSW219F
 FWHM / FWTM 16.0° / 29.0°
 Efficiency 89 %
 Peak intensity 8.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:









LED OSTAR Stage (S2WN)
 FWHM / FWTM 10.0° / 19.0°
 Efficiency 90 %
 Peak intensity 20.8 cd/lm
 LEDs/each optic 1
 Light colour RGBW
 Required components:







LED OSTAR Stage (S2WP)
 FWHM / FWTM 10.0° / 18.0°
 Efficiency 91 %
 Peak intensity 22 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):

<p>SEOUL SEMICONDUCTOR</p> <p>LED SPF05F0A</p> <p>FWHM / FWTM 10.0° / 19.0°</p> <p>Efficiency 89 %</p> <p>Peak intensity 21.6 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour RGBW</p> <p>Required components:</p>		
<p>SEOUL SEMICONDUCTOR</p> <p>LED SPF05F0B</p> <p>FWHM / FWTM 11.0° / 20.0°</p> <p>Efficiency 90 %</p> <p>Peak intensity 18.9 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour RGBW</p> <p>Required components:</p>		
<p>SEOUL SEMICONDUCTOR</p> <p>LED SPF05F0C</p> <p>FWHM / FWTM 12.0° / 22.0°</p> <p>Efficiency 89 %</p> <p>Peak intensity 15.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour RGBW</p> <p>Required components:</p>		


OPTICAL RESULTS (SIMULATED):

<p>CREE → LED</p> <p>LED: CLQ6A-TKW FWHM / FWTM: 13.7° / 26.1° Efficiency: 94 % Peak intensity: 12.7 cd/lm LEDs/each optic: 1 Light colour: RGBW Required components:</p>	
<p>CREE → LED</p> <p>LED: XHP35.2 HD FWHM / FWTM: 12.0° / 22.0° Efficiency: 88 % Peak intensity: 15.6 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>CREE → LED</p> <p>LED: XHP50 FWHM / FWTM: 16.0° / 27.0° Efficiency: 91 % Peak intensity: 10.7 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>CREE → LED</p> <p>LED: XM-L RGBW (XMLCTW) FWHM / FWTM: 13.0° / 23.0° Efficiency: 93 % Peak intensity: 15.2 cd/lm LEDs/each optic: 1 Light colour: RGBW Required components:</p>	

OPTICAL RESULTS (SIMULATED):


CREE LED

LED XP-E2
 FWHM / FWTM 10.0° / 19.0°
 Efficiency 92 %
 Peak intensity 23.5 cd/lm
 LEDs/each optic 1
 Light colour Amber
 Required components:




CREE LED

LED XP-G2 HE
 FWHM / FWTM 11.0° / 22.0°
 Efficiency 92 %
 Peak intensity 19.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XQ-E HI
 FWHM / FWTM 14.0° / 24.0°
 Efficiency 90 %
 Peak intensity 14.4 cd/lm
 LEDs/each optic 4
 Light colour RGBW
 Required components:



CREE LED


LED XT-E
 FWHM / FWTM 10.0° / 19.0°
 Efficiency 91 %
 Peak intensity 24.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (SIMULATED):



LUMILEDS

LED LUXEON 7070
 FWHM / FWTM 18.0° / 34.0°
 Efficiency 90 %
 Peak intensity 6.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LUMILEDS

LED LUXEON C
 FWHM / FWTM 18.0 + °
 Efficiency 86 %
 Peak intensity 7.2 cd/lm
 LEDs/each optic 4
 Light colour RGBW
 Required components:




LUMILEDS

LED LUXEON M/MX
 FWHM / FWTM 17.0° / 28.0°
 Efficiency 91 %
 Peak intensity 9.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:







LUMILEDS

LED LUXEON Rubix
 FWHM / FWTM 12.0° / 21.0°
 Efficiency 92 %
 Peak intensity 19.1 cd/lm
 LEDs/each optic 4
 Light colour RGBW
 Required components:



OPTICAL RESULTS (SIMULATED):


<p>LUMILEDS</p> <p>LED: LUXEON Z FWHM / FWTM: 11.0° / 20.0° Efficiency: 91 % Peak intensity: 21 cd/lm LEDs/each optic: 4 Light colour: RGBW Required components:</p>	
<p>NICHIA</p> <p>LED: NV4x144A FWHM / FWTM: 16.0° / 28.0° Efficiency: 89 % Peak intensity: 10 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED: DURIS E 5050 (GW J9LHS1.4M) FWHM / FWTM: 14.0° / 24.0 + 26.0° Efficiency: 93 % Peak intensity: 13.3 cd/lm LEDs/each optic: 1 Light colour: RGBW Required components:</p>	
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED: Duris S8 FWHM / FWTM: 14.0° / 25.0° Efficiency: 92 % Peak intensity: 13.5 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	

OPTICAL RESULTS (SIMULATED):

OSRAM

Opto Semiconductors


LED OSCONIQ P 3737 (2W version)
 FWHM / FWTM 10.0° / 19.0°
 Efficiency 94 %
 Peak intensity 25.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OSRAM


Opto Semiconductors

LED OSLOM Square CSSRM2/CSSRM3
 FWHM / FWTM 10.0° / 19.0°
 Efficiency 93 %
 Peak intensity 25.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LH351B
 FWHM / FWTM 11.0° / 20.0°
 Efficiency 93 %
 Peak intensity 21.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SAMSUNG


LED LH351D
 FWHM / FWTM 12.0° / 24.0°
 Efficiency 92 %
 Peak intensity 16.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (SIMULATED):


SAMSUNG

LED LM28xB Series
 FWHM / FWTM 10.0° / 20.0°
 Efficiency 93 %
 Peak intensity 21.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SEOUL SEMICONDUCTOR

LED Z5M1/Z5M2
 FWHM / FWTM 10.0° / 19.0°
 Efficiency 93 %
 Peak intensity 25.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)