

STRADA-B2

Wide oval beam for area lighting optimized for CREE XT-E. Assembly with installation tape.


SPECIFICATION:

Dimensions 19.6 x 15.5 mm

Height 5.2 mm

Fastening tape, pin

ROHS compliant yes 1



MATERIALS:


ComponentTypeMaterialColourFinishSTRADA-B2Single lensPMMAclearVOSU-WU-M-365-TAPETapeAcrylic foam

ORDERING INFORMATION:

» Box size: 451 x 254 x 197 mm

ComponentQty in boxMOQMPQBox weight (kg)CA13473_STRADA-B2Single lens43202402404.0





See also our general installation guide: www.ledil.com/installation_guide



OPTICAL RESULTS (MEASURED):

CREE . LED

LED XT-E


FWHM / FWTM 119.0 + 40.0°

Efficiency 94 %
Peak intensity 0.6 cd/lm

Peak intensity 0.6 cd/l LEDs/each optic 1

Light colour White

Required components:



WNICHIA

LED NVSW319B


FWHM / FWTM Asymmetric Efficiency 88 %

Peak intensity 0.5 cd/lm

cak interisity 0.5 ca/iii

LEDs/each optic 1 Light colour White

Required components:



SAMSUNG

LED LH351Z

FWHM / FWTM 116.0 + 42.0°


Efficiency 89 %

Peak intensity 0.6 cd/lm

LEDs/each optic 1

Light colour White

Required components:






OPTICAL RESULTS (SIMULATED):

CREE 1 LED

LED XP-G2
FWHM / FWTM Asymmetric
Efficiency 94 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour White

Required components:




OSRAM

Opto Semiconducto

LED OSCONIQ P 3737 (3W version)

FWHM / FWTM Asymmetric
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour White


Required components:



SAMSUNG

LED LH351B
FWHM / FWTM Asymmetric
Efficiency 92 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour White

Required components:





GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405, Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy