

# STRADA-SQ-C

Beam for area and street lighting such as parks and pedestrian walkways. Version with location pins. Assembly with installation tape.

## **SPECIFICATION:**

25.0 x 25.0 mm **Dimensions** 9.9 mm Height Fastening tape, pin yes 🕕 ROHS compliant



## **MATERIALS:**


Material Colour **Finish** Component **Type** STRADA-SQ-C Single lens **PMMA** clear **ROSE-TAPE** Tape Acrylic foam black

#### **ORDERING INFORMATION:**

Component Qty in box MOQ MPQ Box weight (kg) 2058 294 CA16031\_STRADA-SQ-C Single lens 98 8.1

» Box size: 476 x 273 x 292 mm

# **PRODUCT** CA16031\_STRADA-SQ-C



See also our general installation guide: <a href="www.ledil.com/installation\_guide">www.ledil.com/installation\_guide</a>



# **OPTICAL RESULTS (SIMULATED):**


# CREE + LED

LED XHP70 FWHM / FWTM 120.0° / 138.0°

Efficiency 96 %
Peak intensity 0.3 cd/lm

LEDs/each optic 1
Light colour White

Required components:




## CREE \$\(\phi\) LED

LED XM-L2

FWHM / FWTM 119.0° / 139.0°

Efficiency 96 %
Peak intensity 0.3 cd/lm
LEDs/each optic 1
Light colour White

Required components:




#### CREE + LED

LED XT-E

FWHM / FWTM 122.0° / 146.0°

Efficiency 95 %
Peak intensity 0.3 cd/lm
LEDs/each optic 1
Light colour White

Required components:




# **DESCRIPTION** LUMILEDS

LED LUXEON 5050 Square LES

FWHM / FWTM 116.0° / 138.0°
Efficiency 96 %
Peak intensity 0.3 cd/lm
LEDs/each optic 1
Light colour White

Required components:



Published: 15/07/2019



# **OPTICAL RESULTS (SIMULATED):**



LED LUXEON 7070 FWHM / FWTM 115.0° / 138.0°


Efficiency 88 %

Peak intensity 0.3 cd/lm LEDs/each optic 1

Light colour White

Required components:

Protective plate, glass




# **MUMILEDS**

LED LUXEON M/MX FWHM / FWTM 119.0° / 138.0°

Efficiency 95 %
Peak intensity 0.3 cd/lm
LEDs/each optic 1
Light colour White

Required components:




# **MUMILEDS**

LED LUXEON MZ FWHM / FWTM 116.0° / 138.0°

Efficiency 96 %
Peak intensity 0.3 cd/lm
LEDs/each optic 1
Light colour White

Required components:



Published: 15/07/2019



# PRODUCT DATASHEET CA16031\_STRADA-SQ-C

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

5/5

www.ledil.com/ where\_to\_buy