Rectangular Power Connectors



The Bulgin Rectangular Power Connector range offers a reliable, rugged solution for cable to cable applications in harsh environments with its environmentally sealed range of products.

The series has a male and female option, as well as modifications such as enhanced seal retention, protective end caps, shrink boot adapters, welded flange, terminating resistors and a Y-Type connector for the automotive industry.






Standard Rectangular Connectors



- 2, 3, 4, 6, 8 & 12 Contacts
- Male housing
- Socket contacts
- Available in Grey and Black
- Additional options available



PX0100

PX0102

PX0103

PX0104


2

Part Number	Contacts	Key	Termination	Colour	Additional
PX0100S02BK	2	_	Crimp	Black	-
PX0100S02GY	2	-	Crimp	Grey	-
PX0100S03BK	3	-	Crimp	Black	-
PX0100S03GY	3	-	Crimp	Grey	-
PX0100S04BK	4	-	Crimp	Black	-
PX0100S04GY	4	-	Crimp	Grey	-
PX0100S06BK	6	-	Crimp	Black	-
PX0100S06GY	6	-	Crimp	Grey	-
PX0100S08AGY	8	Α	Crimp	Grey	-
PX0100S12AGY	12	Α	Crimp	Grey	-

Standard Rectangular Connectors Male - ESR



- 2 Contacts
- Male housing
- Enhanced seal retention
- Socket contacts
- Available in Black
- Additional options available




Part Number	Contacts	Key	Termination	Colour	Additional	
PX0102S02BK	2	-	Crimp	Black	ESR	

Standard Rectangular Connectors Male - ESR & PEC



- O 2 Contacts
- Male housing
- Enhanced seal retention & protective end cap
- Socket contacts
- Available in Grey
- Additional options available




Key **Termination** Colour **Additional Part Number Contacts** ESR & PEC PX0103S02GY Crimp Grey

Standard Rectangular Connectors Male - ESR & SBA

PX0104S02BK



- 2 Contacts
- Male housing
- Enhanced seal retention & shrink boot adapter
- Socket contacts
- Available in Black
- Additional options available



Black

Part Number	Contacts	Key	Termination	Colour	Additional
PX0104S02RK	2	_	Crimp	Black	ESR & SBA


ESR & SBA



Standard Rectangular Connectors Male - PEC



- O 2, 3, 4, 6, 8 & 12 Contacts
- Male housing
- Protective end cap
- Socket contacts
- Available in Grey and Black
- Additional options available



PX0105

Part Number	Contacts	Key	Termination	Colour	Additional
PX0105S02BK	2	-	Crimp	Black	PEC
PX0105S02GY	2	-	Crimp	Grey	PEC
PX0105S03BK	3	-	Crimp	Black	PEC
PX0105S03GY	3	-	Crimp	Grey	PEC
PX0105S04BK	4	-	Crimp	Black	PEC
PX0105S04GY	4	-	Crimp	Grey	PEC
PX0105S06BK	6	-	Crimp	Black	PEC
PX0105S06GY	6	-	Crimp	Grey	PEC
PX0105S08ABK	8	Α	Crimp	Black	PEC
PX0105S08AGY	8	Α	Crimp	Grey	PEC
PX0105S12AGY	12	Α	Crimp	Grey	PEC
PX0105S12ABK	12	Α	Crimp	Black	PEC


Standard Rectangular Connectors

Male - SBA



2, 3 & 4 Contacts

- Male housing
- Shrink boot adapter
- Socket contacts
- Available in Grey
- Additional options available




PX0108

Part Number	Contacts	Key	Termination	Colour	Additional
PX0108S02GY	2	-	Crimp	Grey	SBA
PX0108S03GY	3	-	Crimp	Grey	SBA
PX0108S04GY	4	-	Crimp	Grey	SBA

Standard Rectangular Connectors Male - TER



- O 3 Contacts
- Male housing
- Terminating resistor
- Socket contacts
- Available in Grey
- Additional options available



DVATT				
	DYC	11	4	ĺ

Part Number	Contacts	Key	Termination	Colour	Additional	
PX0110S03GY	3	_	Crimp	Grev	TER	

PX0101

PX0106

PX0107




Standard Rectangular Connectors

Female



- O 2, 3, 4, 6, 8 & 12 Contacts
- Female Housing
- Plug contacts
- Available in Grey and Black
- Additional options available




Part Number	Contacts	Key	Termination	Colour	Additional
PX0101P02BK	2	_	Crimp	Black	-
PX0101P02GY	2	-	Crimp	Grev	-
PX0101P03BK	3	-	Crimp	Black	_
PX0101P03GY	3	-	Crimp	Grev	-
PX0101P04BK	4	-	Crimp	Black	_
PX0101P04GY	4	-	Crimp	Grev	-
PX0101P06BK	6	-	Crimp	Black	-
PX0101P06GY	6	-	Crimp	Grev	-
PX0101P08ABK	8	Α	Crimp	Black	-
PX0101P08AGY	8	A	Crimp	Grey	-
PX0101P12ABK	12	Α	Crimp	Black	-
PX0101P12AGY	12	A	Crimp	Grev	-

Standard Rectangular Connectors

Female - PEC



- Q 2, 3, 4, 6, 8 & 12 Contacts
- Female Housing
- Protective end cap
- Plug contacts
- Available in Grey and Black
- Additional options available



Part Number	Contacts	Key	Termination	Colour	Additional
PX0106P02BK	2	-	Crimp	Black	PEC
PX0106P02GY	2	-	Crimp	Grey	PEC
PX0106P03BK	3	-	Crimp	Black	PEC
PX0106P03GY	3	-	Crimp	Grey	PEC
PX0106P04BK	4	-	Crimp	Black	PEC
PX0106P04GY	4	-	Crimp	Grey	PEC
PX0106P06BK	6	-	Crimp	Black	PEC
PX0106P06GY	6	-	Crimp	Grey	PEC
PX0106P08ABK	8	Α	Crimp	Black	PEC
PX0106P08AGY	8	Α	Crimp	Grey	PEC
PX0106P12ABK	12	Α	Crimp	Black	PEC
PX0106P12AGY	12	Α	Crimp	Grey	PEC

Standard Rectangular Connectors


Female - PEC & SBA



- ◇ Protective
- Female Housing

3 Contacts

- Protective end cap & shrink boot adapter
- Plug contacts
- Available in Grey
- Additional options available



Part Number	Contacts	Key	Termination	Colour	Additional
PX0107P03GY	3	-	Crimp	Grey	PEC & SBA




Standard Rectangular Connectors

Female - SBA



PX0109

- O 2, 3 & 4 Contacts
- Female Housing
- Shrink boot adapter
- Plug contacts
- Available in Grey and Black
- O Additional options available



Part Number	Contacts	Key	Termination	Colour	Additional
PX0109P02BK	2	-	Crimp	Black	SBA
PX0109P02GY	2	-	Crimp	Grey	SBA
PX0109P03BK	3	-	Crimp	Black	SBA
PX0109P04GY	4	-	Crimp	Grey	SBA


Standard Rectangular Connectors

Female - TER



PX0111

- O 3 Contacts
- O Female Housing
- Terminating resistor
- Plug contacts
- Available in Grey
- Additional options available



Part Number	Contacts	Key	Termination	Colour	Additional
PX0111P03GY	3	-	Crimp	Grey	TER


Standard Rectangular Connectors

Female - WFL



PX0112

- O 2, 3, 4, 8 & 12 Contacts
- Female Housing
- Welded flange
- Plug contacts
- Available in Grey
- Additional options available



Part Number	Contacts	Key	Termination	Colour	Additional
PX0112P02GY	2	-	Crimp	Grey	WFL
PX0112P03GY	3	-	Crimp	Grey	WFL
PX0112P04GY	4	-	Crimp	Grey	WFL
PX0112P08AGY	8	Α	Crimp	Grey	WFL
PX0112P12AGY	12	Α	Crimp	Grey	WFL


Standard Rectangular Connectors

Female - YTY



PX0113

- O 3 Contacts
- Female Housing
- Y-type connector
- Plug contacts
- Available in Grey
- Additional options available



Part Number	Contacts	Key	Termination	Colour	Additional	
PX0113P03GY	3	-	Crimp	Grey	YTY	



Contacts



- O Crimp Plug & Sockets
- O Choice of Gold and Nickel Plated
- Green Stripe available

Part Number	Plating	AWG	Type	Plug / Socket	Additional
SA1000/G	Nickel Plating	14	Solid	Plug	Green Stripe
SA1001/G	Nickel Plating	14	Solid	Socket	Green Stripe
SA1002/G	Nickel Plating	16 - 20	Solid	Plug	Green Stripe
SA1003/G	Nickel Plating	16 - 20	Solid	Socket	Green Stripe
SA1000	Nickel Plating	14	Solid	Plug	-
SA1001	Nickel Plating	14	Solid	Socket	-
SA1002	Nickel Plating	16 - 20	Solid	Plug	_
SA1003	Nickel Plating	16 - 20	Solid	Socket	-
SA1004	Nickel Plating	16 - 20	Stamped	Plug	Bandolier
SA1005	Nickel Plating	16 - 20	Stamped	Socket	Bandolier
SA1006	Nickel Plating	14 - 18	Stamped	Plug	Bandolier
SA1007	Nickel Plating	14 - 18	Stamped	Socket	Bandolier
SA1008	Gold Plating	14 - 18	Stamped	Plug	Bandolier
SA1009	Gold Plating	14 - 18	Stamped	Socket	Bandolier

Wedgelocks



- O Plug & Sockets available
- O 2, 3, 4, 6, 8 & 12 Contact

* Wedgelocks are sold separately and are required for confirmation of alignment of contact. Please refer to the chart above to determine part required: e.g. WLP02 is required for 2 Contact female housings

WLP12

Part Number	Contacts	Plug / Socket	Additional
WLP02	02	Plug	-
WLS02	02	Socket	-
WLS02ENS	02	Socket	Enhanced Seal
WLP03	03	Plug	-
WLS03	03	Socket	-
WLP04	04	Plug	-
WLS04	04	Socket	-
WLP06	06	Plug	-
WLS06	06	Socket	-
WLP08	08	Plug	-
WLS08	08	Socket	-
WLP12	12	Plug	-
WLS12	12	Socket	-

Tooling



- O Crimp tooling available
- Probe extraction tool

Part Number Additional

10000 Crimping tool for heavy of 10001 Probe extraction tool 10002 Crimping tool for Rectan

Crimping tool for heavy duty Rectangular Connectors (series coming soon) Probe extraction tool Crimping tool for Rectangular Connectors



Electrical:

No Contacts: 2, 3, 4, 6, 8 & 12

Current Rating: 13A Voltage Rating: 250V DC

>1000MΩ (@ 500V DC) Insulation Resistance:

Dielectric Strength: <2mA @ 15V AC

Operating

Material

Temperature Range: -25°C to +120°C

Contact Layout (Rear View)

Cycles:

Termination:

Contact Retention:

Mechanical:

Contact Accommodation:

Sealing:

Body Mouldings: Polybutylene Terephthalate, Polyamide

Glass Fiber

Contacts: Copper Alloy Nickel Plated, Copper Alloy

Gold Plated

Rubber Seal: Silicone Rubber RoHS Compliant

MALE







IP68 (with Rear Protection)

14 - 20 AWG 2.5-0.35 mm²

Crimp terminals

100

Size 16: 111N (25 lbs)



0000

5 6 7 8

8 Contact

00000

8 9 10 11 12

Contact Insertion Instructions

Step One:



Use a previously crimped contact and wire and hold just behind the contact barrel.

Step Two:



Line the contact up with the grommet.

Step Three:



Push the contact until a click is felt. Check the contact is in place by gently tugging and confirming alignment. Repeat for number of contacts desired

Step Four:



When contacts are in place, insert the appropriate wedgelock until a click is heard. Once male and female housings are prepared the parts can be mated

PX₀

XXX

X

S







Range

PX0

Body Type

100 = Male 101 = Female

102 = Male Enhanced Seal Retention 103 = Male Enhanced Seal Retention & Protective End Cap

104 = Male Enhanced Seal Retention & Shrink Boot Adapter 105 = Male Protective End Cap

106 = Female Protective End Cap 107 = Female Protective End Cap & Shrink Boot Adapter 108 = Male Shrink Boot Adapter 109 = Female Shrink Boot Adapter

110 = Male Terminating Resistor 111 = Terminating Resistor 112 = Female Welded Flange 113 = Female Y Type

Contact Type Contacts

intact Type	Contact
= Socket	02
P = Plug ¦	03
	04
	06
	08
1	10

Key

A = A Key

Colour

GY = Grev BK = Black