# TRIPP-LITE by FitoN

1000 Eaton Boulevard Cleveland, OH 44122 United States

## Smart 216 16-Port Multi-User Cat5 KVM Switch for Rack Environments

#### MODEL NUMBER: 0SU22090







#### Description

Multi-user access and control of many computers/servers

Straightforward set up

Space saving devices that eliminate cable clutter

From server rooms to data centers

#### Features

- 16 Ports with 2 simultaneous KVM Users
- BIOS level access
- USB keyboard and mouse console
- Multi-platform PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

### **Specifications**

#### Highlights

- 16 Ports with 2 simultaneous KVM Users
- BIOS level access
- USB keyboard and mouse console
- Multi-platform PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

#### **System Requirements**

#### **Operating System**

 Windows, Novell, Linux, SUN Solaris

#### Resolution

• Supports video resolutions up to 1600 x 1200 @ 85Hz

#### **Package Includes**

- Smart 216
- Power Cord
- RS232 Cable
- Rackmount Hardware
- Owner's Manual



1000 Eaton Boulevard Cleveland, OH 44122 United States

| OVERVIEW                               |                            |
|--|----------------------------|
| UPC Code                               | 654518209914               |
| PHYSICAL                               |                            |
| Color                                  | Black                      |
| Shipping Dimensions (hwd / in.)        | 5.30 x 13.00 x 19.80       |
| Shipping Dimensions (hwd / cm)         | 13.46 x 33.02 x 50.29      |
| Shipping Weight (lbs.)                 | 7.20                       |
| Shipping Weight (kg)                   | 3.27                       |
| Unit Dimensions (hwd / in.)            | 1.700 x 17.000 x 10.600    |
| Unit Dimensions (hwd / cm)             | 4.4 x 43.1 x 27            |
| Unit Weight (Ibs.)                     | 5.1                        |
| Unit Weight (kg)                       | 2.31                       |
| ENVIRONMENTAL                          |                            |
| Storage Temperature Range              | -40 to 70 C / -40 to 158 F |
| Relative Humidity                      | 80% Non-Condensing         |
| Operating Temperature                  | 0 to 40 C / 32 to 104 F    |
| COMMUNICATIONS                         |                            |
| Port Control                           | Hotkeys, OSD               |
| IP Remote Access                       | Yes                        |
| CONNECTIONS                            |                            |
| Number of Ports                        | 16                         |
| Computer/Server Ports                  | 16                         |
| PC/Server Connections                  | VGA; USB; PS/2             |
| FEATURES & SPECIFICATIONS              |                            |
| Cat5 KVM Switch                        | Yes                        |
| NIAP-Certified Secure                  | No                         |
| Number of Users                        | 2                          |
| WARRANTY & SUPPORT                     |                            |
| Product Warranty Period<br>(Worldwide) | 3-year limited warranty    |



1000 Eaton Boulevard Cleveland, OH 44122 United States



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.