

FireWire ® - 6-ft. Firewire IEEE 1394 Gold 4Pin/4Pin Cable

MODEL NUMBER: F009-006-R



Highlights

- Premium quadruple-shielded cables with tinned copper braid and aluminum mylar foil on each twisted pair as well as on the cable as a whole
- Gold plated connectors provide superior conductivity
- Retail Packaging

System Requirements

 Two Firewire 1394 devices with 4-Pin connectors

Package Includes

 6 Foot External Firewire (IEEE 1394) Cable 4 Pin to 4 Pin. with Gold Connectors

Description

Tripp Lite's new Firewire series is a perfect compliment to your connectivity solutions. This 6ft. IEEE-1394 Firewire cable has 4-pin male to 4-pin male connectors supports data transmission of 100~400Mbps and is used most commonly to connect an A/V device to an A/V device. Firewire cables have gold-plated connectors and gold-plated copper contacts for superior conductivity. Premium double-shielded cable with both a braid and a foil shield to virtually eliminate crosstalk and reduce EMI/RFI interference. Tripp Lite warrants this product to be free from defects in materials and workmanship for life. Clamshell retail packaging.

Features

- All Tripp Lite Firewire (IEEE 1394) cabling includes superior foil shielding for reliable error-free data communications
- Firewire cable meets IEEE 1394 standards as set by the institute of electrical and electronic engineers.
- Premium quadruple-shielded cables with tinned copper braid and aluminum
- Mylar foil on each twisted pair as well as on the cable as a whole.
- Gold plated connectors provide superior conductivity.
- Supports data transmission of 100~400Mbps
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Specifications

OVERVIEW		
UPC Code	037332012043	
PHYSICAL		
Cable Length (ft.)	6	
Cable Length (m)	1.83	



Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) 16.51 x 14.60 x 3.18 Shipping Weight (lbs.) 0.29 Shipping Weight (kg) 0.13 CONNECTIONS Side A - Connector 1 4 PIN (MALE) Side B - Connector 1 4 PIN (MALE)			
Shipping Weight (lbs.) 0.29 Shipping Weight (kg) 0.13 CONNECTIONS Side A - Connector 1 4 PIN (MALE) Side B - Connector 1 4 PIN (MALE)	Shipping Dimensions (hwd / in.)	6.50 x 5.75 x 1.25	
Shipping Weight (kg) 0.13 CONNECTIONS Side A - Connector 1 4 PIN (MALE) Side B - Connector 1 4 PIN (MALE)	Shipping Dimensions (hwd / cm)	16.51 x 14.60 x 3.18	
CONNECTIONS Side A - Connector 1 4 PIN (MALE) Side B - Connector 1 4 PIN (MALE)	Shipping Weight (lbs.)	0.29	
Side A - Connector 1 4 PIN (MALE) Side B - Connector 1 4 PIN (MALE)	Shipping Weight (kg)	0.13	
Side B - Connector 1 4 PIN (MALE)	CONNECTIONS		
	Side A - Connector 1	4 PIN (MALE)	
WARRANTY & SUPPORT	Side B - Connector 1	4 PIN (MALE)	
Product Warranty Period (Worldwide) Lifetime limited warranty	Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.