

Center Plate Insert, Decora Style - Vertical, 2 Ports

MODEL NUMBER: N042D-002V-WH



Clean, simple insert mounts within Decora-style wall plate for terminating in-wall audio/video, voice or Ethernet cable installations.

Features

Decora-Style Face Plate Connects Audio/Video, Voice and Data Cable Lines at the Wall This vertical-style center insert provides a clean, simple method for your premise wiring applications, including home theater (audio/video), VoIP phones (voice) and Ethernet (data). Any type of keystone jack, including those used in HDMI, DisplayPort, RCA, USB and Cat5e/6/6a installations, snaps easily into the cutouts for quick cable connection.

High-Impact Construction Designed to Blend In Seamlessly The Decora-style polycarbonate insert plate is white and blends elegantly into any home or office décor for a sleek, professional installation. Mounting screws are included for flush mounting the insert with a Tripp Lite or other compatible Decora-style wall plate (sold separately).

Specifications

| OVERVIEW | |
|--------------------------|--|
| UPC Code | 037332249708 |
| Technology | Cat5/5e; Cat6; Cat6a; DisplayPort; HDBaseT; HDMI; USB 2.0 (High Speed) |
| Country/Region | Global |
| PHYSICAL | |
| Color | White |
| Material of Construction | ABS |
| Total Number of Ports | 2 |

Highlights

- Ideal for home theater, VoIP or Ethernet premise wiring installations
- Compatible with any type of keystone jack, including HDMI, Cat5/6, USB and DisplayPort
- High-impact polycarbonate construction designed to last long in your décor
- Hardware included for mounting flush with compatible Decora-style wall plate

Applications

- Complete your premise wiring application with a clean, sleek-looking Decora-style appearance

Package Includes

- N042D-002V-WH Center Plate Insert, Decora Style - Vertical, 2 Ports
- (2) Mounting screws

| ENVIRONMENTAL | |
|-------------------------------------|---|
| Operating Temperature Range | 14 to 140 F (-10 to 60 C) |
| Storage Temperature Range | -40 to 154 F (-40 to 68 C) |
| Relative Humidity | 10% to 90% (Non-Condensing) |
| CONNECTIONS | |
| Number of Ports | 2 |
| Side A - Connector 1 | KEYSTONE JACK CUTOUT |
| Side B - Connector 1 | KEYSTONE JACK CUTOUT |
| FEATURES & SPECIFICATIONS | |
| Antibacterial | No |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS; REACH; Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |