

1-Port European-Style Insert, Unloaded Shuttered Angled Module, Icon Tab, White

MODEL NUMBER: N042E-WM1-SAT



European-style insert accepts a compatible keystone jack for terminating premise audio/video, voice or data applications.

Features

European Insert Connects Your In-Wall Audio/Video, Voice or Data Cable Application

This Europe-style insert with unloaded shuttered angled module is ideal for your premise wiring applications, including home theater, VoIP phones and Ethernet. Just snap a keystone jack, including one used in HDMI, DisplayPort, RCA audio, USB and Cat5e/6/6a applications, into the plate's cutout for immediate cable connection. Compatible with Tripp Lite's N042E-WF1 gang frame, the angled module facilitates easy cable installation in tight spaces without excessive bending.

High-Impact Construction Designed to Blend In Seamlessly with Your Room

This white module is shuttered to resist dust. It measures 45 x 45 millimeters and blends elegantly into any home or office décor for a sleek, professional installation. The ABS plastic construction meets UL 94V-0 flame-retardant standards for protection against fire and high heat. Use the icon tab to quickly identify the connected port.

Highlights

- Ideal for home theater, VoIP or Ethernet in-wall wiring installations
- High-impact plastic construction designed to blend in with your home/office décor
- White insert measures 45 x 45 mm for a sleek, professional appearance
- Angled design allows easier installation in crowded spaces without damaging the cable

Package Includes

N042E-WM1-SAT 1-Port Europe-Style Insert, White

Specifications

| OVERVIEW | |
|--------------------------|--|
| UPC Code | 037332268914 |
| Technology | Cat5/5e; Cat6; Cat6a; DisplayPort; HDBaseT; HDMI; USB 2.0 (High Speed) |
| Country/Region | Europe |
| PHYSICAL | |
| Color | White |
| Material of Construction | Spring: SUS304; All else: ABS (UL94V-0) |
| Total Number of Ports | 1 |

| | |
|--------------------------------------|---|
| Unit Dimensions (hwd / in.) | 1.772 x 1.772 x 0.335 |
| Finish | Matte |
| ENVIRONMENTAL | |
| Operating Temperature Range | 14 to 140 F (-10 to 60 C) |
| Storage Temperature Range | -40 to 154 F (-40 to 68 C) |
| Operating Humidity Range | 10% to 90% RH, (Non-Condensing) |
| Storage Humidity Range | 10% to 90% RH, (Non-Condensing) |
| CONNECTIONS | |
| Number of Ports | 1 |
| Side A - Connector 1 | KEYSTONE JACK CUTOUT |
| FEATURES & SPECIFICATIONS | |
| Antibacterial | No |
| STANDARDS & COMPLIANCE | |
| Product Certifications | UL 94; UL Listed; cUL Listed |
| Product Compliance | RoHS; REACH; Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |