

## 2-Port European-Style Insert, Unloaded Shuttered Angled Module, Icon Tabs, White

MODEL NUMBER: **N042E-WM2-SAT**



### Highlights

- Ideal for home theater, VoIP or Ethernet in-wall wiring installations
- High-impact plastic construction designed to blend in with your home/office décor
- White insert measures 45 x 45 mm for a sleek, professional appearance
- Angled design allows easier installation in crowded spaces without damaging the cable

### Package Includes

N042E-WM2-SAT 2-Port  
European-Style Insert, White

European-style insert accepts compatible keystone jacks for terminating premise audio/video, voice or data applications.

### Features

#### European Insert Connects Your In-Wall Audio/Video, Voice or Data Cable Application

This European-style insert with unloaded shuttered angled module is ideal for your premise wiring applications, including home theater, VoIP phones and Ethernet. Just snap keystone jacks, including those used in HDMI, DisplayPort, RCA audio, USB and Cat5e/6/6a applications, into the cutouts for immediate cable connection. Compatible with Tripp Lite's N042E-WF1 gang frame, the angled module facilitates easy cable installation in tight spaces without excessive bending.

#### High-Impact Construction Designed to Blend In Seamlessly with Your Room

This white module is shuttered to resist dust. It measures 45 x 45 millimeters and blends elegantly into any home or office décor for a sleek, professional installation. The ABS plastic construction meets UL 94V-0 flame-retardant standards for protection against fire and high heat. Use the icon tabs to quickly identify the connected ports.

## Specifications

| OVERVIEW                 |  |
|--------------------------|--|
| UPC Code                 | 037332268921   |
| Technology               | Cat5/5e; Cat6; Cat6a; DisplayPort; HDBaseT; HDMI; USB 2.0 (High Speed) |
| Country/Region           | Europe   |
| PHYSICAL                 |  |
| Color                    | White  |
| Material of Construction | Spring: SUS304; All else: ABS (UL94V-0)                                |
| Total Number of Ports    | 2  |

|                                      |   |
|--------------------------------------|---|
| Unit Dimensions (hwd / in.)          | 1.776 x 1.776 x 1.016                   |
| Finish                               | Matte                                   |
| <b>ENVIRONMENTAL</b>                 |   |
| Operating Temperature Range          | 14 to 140 F (-10 to 60 C)               |
| Storage Temperature Range            | -40 to 154 F (-40 to 68 C)              |
| Operating Humidity Range             | 10% to 90% RH, (Non-Condensing)         |
| Storage Humidity Range               | 10% to 90% RH, (Non-Condensing)         |
| <b>CONNECTIONS</b>                   |   |
| Number of Ports                      | 2                                       |
| Side A - Connector 1                 | (2) KEYSTONE JACK CUTOUT                |
| <b>FEATURES &amp; SPECIFICATIONS</b> |   |
| Antibacterial                        | No                                      |
| <b>STANDARDS &amp; COMPLIANCE</b>    |   |
| Product Certifications               | UL 94; UL Listed; cUL Listed            |
| Product Compliance                   | RoHS; REACH; Trade Agreements Act (TAA) |
| <b>WARRANTY &amp; SUPPORT</b>        |   |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty               |