

AC Power Supply for Tripp Lite N785-CH12 Media Converter Chassis, 75W

MODEL NUMBER: N785-CH75W-AC



75W AC power supply provides primary or redundant power to your media converter installation.

Features

Powers Your Tripp Lite N785-CH12 12-Port Media Converter Chassis

This 75-watt AC power supply works with the Tripp Lite N785-CH12 media converter chassis to provide redundant power that helps prevent unwanted and expensive downtime. One N785-CH75W-AC comes pre-installed with the N785-CH12 to provide primary power. An additional power supply is also recommended as a replacement part.

Specifications

OVERVIEW	
UPC Code	037332267061
Accessory Type	Power Supply
Accessory Class	Networking Accessories
DISPLAY	
Accessories (Included)	Fuse Glass Tube (x2)
POWER	
Power Source Type	AC Adapter
External Power Supply Plug(s)	NEMA 5-15P North America
External Power Supply Input Specs (V / Hz / A)	90-240V / 50/60Hz / 2A
External Power Supply Output Specs (V / A)	12V / 6.5A

Highlights

- Supplies AC power to a media converter installation using Tripp Lite's N785-CH12
- Multiple power supplies provide primary and redundant power to prevent downtime

System Requirements

Tripp Lite N785-CH12 Media Converter Chassis

Package Includes

N785-CH75W-AC 75W AC Power Supply

External Power Supply Cord Length (ft.)	6
External Power Supply Cord Length (m.)	1.83
PHYSICAL	
Power Cord Color	Black
Unit Dimensions (hwd / in.)	5.240 x 2.320 x 9.060
Unit Dimensions (hwd / cm)	13.3 x 5.9 x 23.0
Unit Packaging Type	Box
ENVIRONMENTAL	
Operating Temperature Range	32 to 122F (0 to 50C)
Storage Temperature Range	-4 to 185F (-20 to 85C)
Operating Humidity Range	20% to 90%
Storage Humidity Range	20% to 90%
FEATURES & SPECIFICATIONS	
Auto MDIX Support	No
IP68 Rated	No
IP20 Rated	No
STANDARDS & COMPLIANCE	
External Power Supply Certifications	CE; FCC; RoHS
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA); Trade Agreements Act (TAA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty