

## Power Cord C14 to C15 - Heavy-Duty, 15A, 250V, 14 AWG, 6 ft. (1.83 m), Black

MODEL NUMBER: P018-006



Connect network hardware with C15 power connections such as servers to PDUs and UPS systems with C14 type inputs.

### Features

- Heavy-duty power cord supports up to 250V
- Flexible 14AWG wire for easy routing
- Use with Cisco, HP and other hardware that uses C15 type power connections
- UL Listed

## Specifications

| OVERVIEW                    |                          |
|-----------------------------|--------------------------|
| UPC Code                    | 037332168443             |
| Device Compatibility        | Network Switch; UPS; PDU |
| Country/Region              | North America            |
| INPUT                       |                          |
| Maximum Input Amps          | 15                       |
| Voltage Compatibility (VAC) | 100-250                  |
| PHYSICAL                    |                          |
| Plug Color                  | Black                    |
| Cable Jacket Color          | Black                    |
| Cable Jacket Material       | PVC                      |

### Highlights

- 6-ft. heavy-duty power cord, C14-to-C15
- 100-250V, 15A, 14AWG, SJT
- UL Listed

### Package Includes

- 6-ft. C14 to C15 Power Cord

|                                      |                           |
|--------------------------------------|---------------------------|
| Cable Jacket Rating                  | VW-1                      |
| Power Cord Jacket Type               | SJT                       |
| Cable Outer Diameter (OD)            | 9.3mm                     |
| Number of Conductors                 | 3                         |
| Wire Gauge (AWG)                     | 14                        |
| Wire Gauge (OD - mm <sup>2</sup> )   | 2.08                      |
| Cable Length (ft.)                   | 6                         |
| Cable Length (m)                     | 1.83                      |
| Shipping Dimensions (hwd / in.)      | 1.00 x 7.00 x 11.00       |
| Shipping Dimensions (hwd / cm)       | 2.54 x 17.78 x 27.94      |
| Shipping Weight (lbs.)               | 0.76                      |
| Shipping Weight (kg)                 | 0.34                      |
| <b>ENVIRONMENTAL</b>                 |                           |
| Operating Temperature Range          | -4 to 140 F (-20 to 60 C) |
| Storage Temperature Range            | -4 to 140 F (-20 to 60 C) |
| Operating Humidity Range             | 10% to 65% RH             |
| Storage Humidity Range               | 10% to 65% RH             |
| <b>CONNECTIONS</b>                   |                           |
| Side A - Connector 1                 | IEC-320-C14               |
| Side B - Connector 1                 | IEC-320-C15               |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                           |
| Antibacterial                        | No                        |
| Angled Plug                          | No                        |
| High Voltage                         | Yes                       |
| Locking Plug                         | No                        |
| Coiled Power Cord                    | No                        |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                           |
| Product Certifications               | cUL Listed; UL Listed     |
| Product Compliance                   | RoHS                      |
| <b>WARRANTY &amp; SUPPORT</b>        |                           |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty |



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States



© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.