

Power Cord, NEMA 5-15P to Right-Angle C15 - Heavy-Duty, 15A, 125V, 14 AWG, 8 ft. (2.43 m), Black

MODEL NUMBER: P019-008-C15RA











C15 right-angle power cable connects a PoE network switch or other device with a C16 power inlet in tight spaces or awkward angles.

Features

IEC C15 Power Cord for Network Devices That Require a Heavy-Gauge ConnectionThis IEC C15 power cable features 14 AWG wire suitable for high power connections, making it reliable for large server applications that require a higher-rated, heavier-gauge cable. The C15 connector is designed for higher-temperature devices, such as electric kettles, PoE (Power over Ethernet) switches with high-wattage power supplies, and similar network components. This cord can also replace or upgrade the standard power cord provided by the device's manufacturer. The 8-ft. (2.43 m) length allows you flexibility in placing equipment with respect to the power outlet.

Right-Angle C15 Plug Makes Connecting in Tight Spaces EasierThe C15 right-angle power cable is easier to install in confined spaces, such as the back of a rack enclosure cabinet. When plugged in, the right-angled C15 plug guides the cable parallel to your peripheral, allowing you to push the device up against a wall or hide it behind a desk to maximize space.

Highlights

- Right-angle C15 plug allows easier connection in confined or hard-to-reach spaces
- Recommended for powering PoE switches with high-wattage power supplies
- 8-ft. (2.43 m) length allows flexibility in placing devices in relationship to AC outlet
- NEMA 5-15P to C15 cable replaces or upgrades original manufacturer's power cord
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect devices like highwattage PoE switches to a PDU up to 8-ft. (2.43 m) away in your data center
- Extend an existing power connection up to 8-ft. (2.43 m) to more easily place a device or reach a power source
- Update or replace the standard power cord provided by a device's original manufacturer
- Power a device located in a hard-to-access area behind a desk or flush against a wall

Package Includes

 P019-008-C15RA 5-15P to Right-Angle C15 Power Cord, 8ft. (2.43 m), Black

Specifications

OVERVIEW		
UPC Code	037332202413	
Device Compatibility	Computer; Server; Network Switch; UPS; PDU	
Country/Region	North America	
INPUT		
INFOI		
Maximum Input Amps	15	
Voltage Compatibility (VAC)	125	



Plug Color Black Cable Jacket Color Black Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Jacket Rating SJT Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (IT) 8 Cable Length (IT) 8 Cable Length (IT) 0.50 x 11.80 x 14.00 Shipping Dimensions (Invid / cm) 1.27 x 29.97 x 35.56 Shipping Dimensions (Invid / cm) 1.27 x 29.97 x 35.56 Shipping Weight (Ibs.) 1.00 Shipping Weight (Ibs.) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Operating Temperature Range -4 to 140 F (-20 to 60 C) Oberating Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 NEG-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS An			
Gable Jacket Color Black PVC Cable Jacket Material PVC Cable Jacket Rating VW+1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft) 8 Cable Length (ft) 8 Cable Length (ft) 0.50 × 11.80 × 14.00 Shipping Dimensions (hwd / in) 0.50 × 11.80 × 14.00 Shipping Dimensions (hwd / in) 0.27 × 29.97 × 35.56 Shipping Weight (bs.) 1.00 Shipping Weight (bs.) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Colled Power Cord No STANDARDS & COMPLIANCE	PHYSICAL		
Cable Jacket Material PVC Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Numb	Plug Color	Black	
Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 8 Gable Length (ft.) 8 Gable Length (m) 2.44 Shipping Dimensions (hwd / in.) 0.50 x 11.80 x 14.00 Shipping Dimensions (hwd / om) 1.27 x 29.97 x 35.56 Shipping Weight (ibs.) 1.00 Shipping Weight (kg) 0.46 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 – RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Colled Power Cord No STANDARDS & COMPLIANCE	Cable Jacket Color	Black	
Power Cord Jacket Type SJT Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (AWG) 2.08 Cable Length (ft.) 8 Cable Length (ft.) 8 Cable Length (m) 2.44 Shipping Dimensions (ftwd / in.) 0.50 x 11.80 x 14.00 Shipping Dimensions (ftwd / em) 1.27 x 29.97 x 35.56 Shipping Weight (bs.) 1.00 Shipping Weight (kg) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Colled Plug No Colled Power Cord No STANDARDS & COMPLIANCE	Cable Jacket Material	PVC	
Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft) 8 Gable Length (m) 2.44 Shipping Dimensions (ftwd / in.) 0.50 x 11.80 x 14.00 Shipping Dimensions (ftwd / or.) 1.27 x 29.97 x 35.56 Shipping Weight (fbs.) 1.00 Shipping Weight (kg) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Temperature Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE	Cable Jacket Rating	VW-1	
Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 8 Cable Length (ft.) 0.50 × 11.80 × 14.00 Shipping Dimensions (twd / in.) 0.50 × 11.80 × 14.00 Shipping Dimensions (twd / orn) 1.27 × 29.97 × 35.56 Shipping Weight (lbs.) 1.00 Shipping Weight (kg) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Colled Power Cord No STANDARDS & COMPLIANCE	Power Cord Jacket Type	SJT	
Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 8 Cable Length (m) 2.44 Shipping Dimensions (hwd / m.) 0.50 x 11.80 x 14.00 Shipping Dimensions (hwd / cm) 1.27 x 29.97 x 35.56 Shipping Weight (lbs.) 1.00 Shipping Weight (kg) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE	Cable Outer Diameter (OD)	9.2mm	
Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 8 Cable Length (m) 2.44 Shipping Dimensions (hwd / in.) 0.50 x 11.80 x 14.00 Shipping Dimensions (hwd / cm) 1.27 x 29.97 x 35.56 Shipping Weight (lbs.) 1.00 Shipping Weight (kg) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Colled Power Cord No STANDARDS & COMPLIANCE	Number of Conductors	3	
Cable Length (ft.) 8 Cable Length (m) 2.44 Shipping Dimensions (hwd / in.) 0.50 x 11.80 x 14.00 Shipping Dimensions (hwd / cm) 1.27 x 29.97 x 35.56 Shipping Weight (lbs.) 1.00 Shipping Weight (kg) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Colled Power Cord No	Wire Gauge (AWG)	14	
Cable Length (m) 2.44 Shipping Dimensions (hwd / rin.) 0.50 x 11.80 x 14.00 Shipping Dimensions (hwd / cm) 1.27 x 29.97 x 35.56 Shipping Weight (lbs.) 1.00 Shipping Weight (kg) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE	Wire Gauge (OD - mm²)	2.08	
Shipping Dimensions (hwd / in.) 0.50 x 11.80 x 14.00 Shipping Dimensions (hwd / cm) 1.27 x 29.97 x 35.56 Shipping Weight (lbs.) 1.00 Shipping Weight (kg) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Cocking Plug No	Cable Length (ft.)	8	
Shipping Dimensions (hwd / cm) 1.27 x 29.97 x 35.56	Cable Length (m)	2.44	
Shipping Weight (kg) 1.00 Shipping Weight (kg) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Colied Power Cord No STANDARDS & COMPLIANCE	Shipping Dimensions (hwd / in.)	0.50 x 11.80 x 14.00	
Shipping Weight (kg) 0.45 ENVIRONMENTAL Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Coiled Power Cord No STANDARDS & COMPLIANCE	Shipping Dimensions (hwd / cm)	1.27 x 29.97 x 35.56	
ENVIRONMENTAL Operating Temperature Range	Shipping Weight (lbs.)	1.00	
Operating Temperature Range -4 to 140 F (-20 to 60 C) Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 – RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Coiled Power Cord No STANDARDS & COMPLIANCE	Shipping Weight (kg)	0.45	
Storage Temperature Range -4 to 140 F (-20 to 60 C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 – RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	ENVIRONMENTAL		
Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 – RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No	Operating Temperature Range	-4 to 140 F (-20 to 60 C)	
Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No	Storage Temperature Range	-4 to 140 F (-20 to 60 C)	
CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 – RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No	Operating Humidity Range	10% to 65% RH	
Side A - Connector 1 NEMA 5-15P Side B - Connector 1 IEC-320-C15 - RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Storage Humidity Range	10% to 65% RH	
Side B - Connector 1 IEC-320-C15 – RIGHT ANGLE FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	CONNECTIONS		
FEATURES & SPECIFICATIONS Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Side A - Connector 1	NEMA 5-15P	
Antibacterial No Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No	Side B - Connector 1	IEC-320-C15 – RIGHT ANGLE	
Angled Plug Yes High Voltage No Locking Plug No Coiled Power Cord No	FEATURES & SPECIFICATIONS		
High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Antibacterial	No	
Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Angled Plug	Yes	
Coiled Power Cord No STANDARDS & COMPLIANCE	High Voltage	No	
STANDARDS & COMPLIANCE	Locking Plug	No	
	Coiled Power Cord	No	
	STANDARDS & COMPLIANCE		
Product Certifications COL Listed; UL Listed	Product Certifications	cUL Listed; UL Listed	



Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.