

Safe-IT High-Speed HDMI Antibacterial Cable with Ethernet (M/M), UHD 4K 60 Hz, 4:4:4, Black, 6 ft. (1.83 m)

MODEL NUMBER: P569AB-006











HDMI cable with antibacterial properties connects audio/video components to a 4K display in your home theater or digital signage application.

Features

4K HDMI Cable Connects Home Theater or Digital Signage Audio/Video Components

This high-speed HDMI cable securely connects laptops, tablets, PCs, Blu-ray players, game consoles, Roku/Apple TV boxes, satellite/cable TV receivers and other devices with HDMI outputs to HDTVs, HD monitors, projectors or home theater receivers with HDMI inputs. It also supports Ethernet, so no separate cable is needed to connect devices online. The 4K P569AB-006 is backward compatible with all your existing HDMI devices.

Provides Extra Protection Against Certain Bacteria

The molded connectors and PVC jacket are constructed using an antibacterial material that is effective in inhibiting the growth of Escherichia coli (E. coli) and Staphylococcus aureus (staph). This added protection makes this cable an ideal solution for medical facilities, schools, businesses, restaurants/kitchens and anywhere else that needs extra protection against bacteria.

Transmits Crystal-Clear True 4K Video with Audio and 4:4:4 Color

The P569AB- $\dot{0}$ 06 supports Ultra HD resolutions up to 4K and 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor.

Premium Construction for Superior Performance

The P569AB-006 features foil and braid shielding that ensures reliable, error-free signal quality and protection from EMI/RFI line noise that can distort or destroy data. Gold-plated connectors provide maximum conductivity and minimum data loss to guarantee a clear transmission free of interference. Integral strain relief gives the cable extra flexibility, reduces stress and helps the cable move freely without cracking or breaking loose from the connector.

Specifications

OVERVIEW

Highlights

- Supports UHD resolutions up to 4K (4:4:4) for crystal-clear video
- Made with antibacterial material proven effective in inhibiting the growth of E. coli and staph
- Foil/braid shielding protects against EMI/RFI line noise that can distort or destroy data
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Watch 4K video from a Blu-ray player, game console, laptop or tablet on a 4K television, monitor or projector
- Provide extra protection against bacteria to give cable installers and IT personnel peace of mind during installation
- Connect a Chromebook or MacBook to a conference table's A/V box to give a video presentation on a large screen
- Play online or PC video games that display optimal graphics
- Send 4K video content to digital signs or point-of-sale displays

Package Includes

P569AB-006 High-Speed HDMI Antibacterial Cable with Ethernet, M/M, Black, 6 ft.



Storage Temperature Range	-40 to 176 F (-40 to 80 C)
Operating Temperature Range	32 to 113 F (0 to 45 C)
ENVIRONMENTAL	
Minimum Bend Radius	60mm
Ferrite Core	No Section 1 and 1
Cable Length (in.)	72
Cable Length (m)	1.83
Cable Length (ft.)	6
Wire Gauge (AWG)	30
Cable Outer Diameter (OD)	6.0 mm
Cable Jacket Rating	VW-1
Cable Jacket Material	PVC
Connector Color	Black
Cable Jacket Color	Black
Material of Construction	PVC
Color	Black
PHYSICAL	
LED Indicators	0
USER INTERFACE, ALERTS & CONTROLS	
Audio Specification	Stereo Audio
AUDIO	
Signal Transmission	Bidirectional
EDID Support	Yes
Chroma Sub Sampling	4:4:4
3D Video Supported	Yes
HDR Support	No V
Max Supported Color Depth	24-bit True Color
Max Supported Video Resolution	3840 x 2160 @ 60Hz
VIDEO	
Cable Type	
Cable Type	Passive
Technology	HDMI
UPC Code	037332261175



Operating Humidity Range	10% to 85% RH, Non-Condensing	
Storage Humidity Range	5% to 90% RH, Non-Condensing	
, , , , , , , , , , , , , , , , , , ,		
COMMUNICATIONS		
Consumer Electronics Control (CEC) Supported	Yes	
CONNECTIONS		
Side A - Connector 1	HDMI (MALE)	
Side B - Connector 1	HDMI (MALE)	
Connector Plating	Gold	
Contact Plating	Gold	
Connector Style	Straight	
Latching or Gripping Connector	No	
FEATURES & SPECIFICATIONS		
Antimicrobial	No	
EMI/RFI Line Noise Protection	No	
MST Support	No	
Antibacterial	Yes	
IP68 Rated	No	
IP20 Rated	No	
Armored Cable	No	
Ethernet Support	Yes	
HDCP Specification	1.4	
Driver Required	No	
STANDARDS & COMPLIANCE		
Product Certifications	CSA (Canada); UL 1778	
Product Compliance	RoHS; CE (Europe); REACH	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	







© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.