TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

Dual DisplayPort KVM Cable Kit - DP, USB, 3.5 mm Audio (3xM/3xM) + DP (M/M), 4K, 4:4:4, 10 ft. (3.05 m), Black

MODEL NUMBER: P783-010-DP





Dual DisplayPort KVM cable kit with DP, USB A/B and 3.5 mm plugs connects your computer to a Tripp Lite B002-DP2A4 or other compatible NIAP KVM.

Features

10-ft. (3.05 m) Cables Connect Your Computer and 2 DisplayPort Monitors to a Tripp Lite NIAP KVM This DisplayPort cable kit includes two 10-ft. (3.05 m) cables for connecting a computer with two monitors to a KVM switch. The P783-010 features DisplayPort, USB A/B and 3.5 mm audio connectors on both ends for connecting your computer to a KVM switch. The P580-010 is a DisplayPort cable with male connectors on each end.

Specifically Designed for Select Tripp Lite KVMs to Save You Time and MoneyRecommended for the Tripp Lite NIAP KVM Series. The cables support DisplayPort video resolutions up to 3840 x 2160 (4K x 2K) at 60 Hz with true 4:4:4 chroma subsampling. They are compatible with HDCP 2.2 and DisplayPort 1.2 standards. The P783-010 also supports USB 2.0 data transfer speeds up to 480 Mbps. By combining several different cables into one convenient kit, you cut down on unnecessary clutter and save money.

Highlights

- Cuts cable clutter and saves money by combining essential KVM cables into just 2
- Includes 10-ft. (3.05 m) DisplayPort cable and 10-ft. (3.05 m) 3-in-1 DP, USB and 3.5 mm audio cable
- Delivers UHD picture quality at resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Supports true 4:4:4 chroma subsampling to meet latest color standards
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Connect a headless computer with dual displays to a Tripp Lite KVM switch
- Upgrade or replace worn or lost KVM cables
- Eliminate clutter and save money by replacing multiple cables with one new kit
- Extend the distance between the KVM switch and computer to 10 ft.

System Requirements

 Tripp Lite B002-DP2A4 NIAP KVM or other compatible KVM switch

Package Includes

- P783-010 DisplayPort KVM cable kit, 3 in 1 (M/M), 10 ft.
- P580-010 DisplayPort monitor cable (M/M), 10 ft.

Specifications

OVERVIEW	
UPC Code	037332241641
Accessory Type	Cable Kit
Technology	DisplayPort
Accessory Class	KVM Switch Accessories



1000 Eaton Boulevard Cleveland, OH 44122 United States

VIDEO		
Max Supported Video Resolution	3840 x 2160 @ 60Hz	
PHYSICAL		
Color	Black	
Cable Jacket Color	Black	
Cable Length (ft.)	10	
Cable Length (m)	3.05	
Cable Length (in.)	120	
Shipping Dimensions (hwd / in.)	12.00 x 10.00 x 0.50	
Shipping Dimensions (hwd / cm)	30.48 x 25.40 x 1.27	
Shipping Weight (lbs.)	1.22	
Shipping Weight (kg)	0.55	
Unit Dimensions (hwd / in.)	0.000 × 0.000 × 0.000	
ENVIRONMENTAL		
Operating Temperature Range	14 ~ 122F (-10 ~ 50C)	
Storage Temperature Range	5 ~ 140F (-15 ~ 60C)	
Relative Humidity	0 ~ 90% RH, Non-Condensing	
CONNECTIONS		
Side A - Connector 1	3.5MM (MALE); DISPLAYPORT (MALE); USB A (MALE)	
Side A - Connector 2	DISPLAYPORT (MALE)	
Side B - Connector 1	3.5MM (MALE); DISPLAYPORT (MALE); USB B (FEMALE)	
Side B - Connector 2	DISPLAYPORT (MALE)	
Contact Plating	Gold	
FEATURES & SPECIFICATIONS		
Displayport Specification	1.2	
HDCP Specification	2.2	
USB Specification	USB 2.0 (up to 480 Mbps)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



1000 Eaton Boulevard Cleveland, OH 44122 United States



© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.