

SCSI/Fibre Channel - 6-ft. SCSI Cable HD68M to centronic 50M Double Shielded

MODEL NUMBER: \$432-006



Highlights

- Premium double-shielded cable
- 34 twisted-pair conductors

System Requirements

 Any external device or SCSI controller card requiring a HD68 or C50 interface

Package Includes

 6-ft. SCSI cable HD68M to Centronic 50M double shielded

Description

Multi-platform SCSI III to I external peripheral cable HD68M/C50M. This 6ft cable is designed to connect two SCSI III (fast and wide) or SCSI I devices together. Manufactured using double shielded 34 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 34 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW		
OVERVIEW		
UPC Code	037332014184	
PHYSICAL		
Cable Length (ft.)	6	
Cable Length (m)	1.83	
Shipping Dimensions (hwd / in.)	11.75 x 7.00 x 0.75	



Shipping Dimensions (hwd / cm)	29.84 x 17.78 x 1.90	
Shipping Weight (lbs.)	0.83	
Shipping Weight (kg)	0.38	
CONNECTIONS		
Side A - Connector 1	HD68 (MALE)	
Side B - Connector 1	CENTRONICS 50 (MALE)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.