

4-Port USB 2.0 USB over Cat5 Hub with 3 local Ports and 1 Remote Port, TAA

MODEL NUMBER: U224-1R4-R









Description

Tripp Lite's U224-1R4-R is a kit that includes a 3-port USB 2.0 local transmitter unit, and a 1-Port USB 1.1 remote receiver unit. Connect up to 3 USB 2.0 devices to the local transmitter, while extending an additional USB 1.1 peripheral up to 150-ft. (45.72 m) from your computer. Simply plug the transmitter into the USB port on your computer, connect your USB peripherals, and run Cat5e/Cat6 cable up to 150-ft. (45.72 m) to the remote receiver unit and connected device. Plug-and-play; no software or drivers required. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- Local transmitter unit features 3 USB 2.0 ports
- Remote receiver unit features 1 USB 1.1 port
- Locate a USB 1.1 peripheral up to 150-ft. (45.72 m) from your computer
- Uses readily available Cat5e/Cat6 patch cable
- Plug-and-play; no software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW		
OVERVIEW		
UPC Code	037332146694	
Product Type	Hub	
Technology	USB 2.0 (High Speed)	
Host Connector	USB A (MALE)	
VIDEO		

Highlights

- Local transmitter unit features 3 USB 2.0 ports
- Remote receiver unit features 1 USB 1.1 port
- Locate a USB 1.1 peripheral up to 150-ft. (45.72 m) from your computer
- Plug-and-play; no software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Package Includes

- 3-port USB 2.0 local transmitter unit
- 1-port USB 1.1 remote receiver unit
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A)
- Owner's manual



Number of Monitors Supported	0	
Extended Mode	No	
Mirror Mode	No	
DATA		
Data Ports	(4) USB A (FEMALE)	
Data Ports Details	(4) USB-A - USB 2.0	
POWER		
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A	
PHYSICAL		
Color	Black	
Receiver Unit Height (in.)	0.9	
Receiver Unit Width (in.)	1.8	
Receiver Unit Depth (in.)	2.6	
Shipping Dimensions (hwd / in.)	2.30 x 5.90 x 8.90	
Shipping Dimensions (hwd / cm)	5.84 x 14.99 x 22.61	
Shipping Weight (lbs.)	0.80	
Shipping Weight (kg)	0.36	
Transmitter Unit Depth (in.)	3.3	
Transmitter Unit Height (in.)	0.9	
Transmitter Unit Width (in.)	2.4	
CONNECTIONS		
Number of Ports	4	
Side A - Connector 1	USB A (MALE)	
Side A - Connector 2	RJ45 (FEMALE)	
Side B - Connector 1	(4) USB A (FEMALE)	
Side B - Connector 2	RJ45 (FEMALE)	
STANDARDS & COMPLIANCE		
Product Compliance	Trade Agreements Act (TAA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	







© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.