

USB 3.0 SuperSpeed Adapter - USB-A to USB-A, M/F, Up Angle, Black

MODEL NUMBER: U324-000-UP







Converts a standard USB port into a more convenient up-angled USB port in tight spaces, such as behind furniture or against a wall.

Features

One-Piece Adapter Connects Computers, Printers, Modems and Other USB EquipmentThis palm-sized USB adapter connects your computer, laptop or other compatible USB-A device, such as a Chromebook or Surface Pro tablet, to a USB-A keyboard, printer, portable hard drive, flash drive, patch panel or other peripheral. It supports USB 3.0 data transfer speeds up to 5 Gbps, which is 10 times faster than USB 2.0. The fully molded piece is small enough to carry in your pocket, purse or laptop bag.

Up-Angle USB-A Port Makes Connecting and Disconnecting Easier in Tight SpacesThe female USB connector is designed at a 90-degree up angle, which makes it easier to reach in from above to connect cables where space is at a premium. This helps you, for instance, save space in your workspace by letting you push your PC flush against the wall or the back of a cabinet. Instead of leaving space in the rear for protruding USB cables, the U324-000-UP allows you to connect cables parallel to your computer.

Highlights

- Recommended for powering computers, printers and other home/office peripherals
- 90-degree-angled form factor is ideal for tight spaces, such as flush against a wall
- Supports USB 3.0 SuperSpeed data transfer rates up to 5 Gbps—10x faster than USB 2.0
- Durable one-piece molded adapter fits easily in pocket or bag for connecting anywhere
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Connect devices like computers, servers and external hard drives in your data center, workspace or home theater
- Create a USB connection in a hard-to-reach space, such as against a wall or behind a desk

Package Includes

 U324-000-UP USB 3.0 SuperSpeed Adapter

Specifications

OVERVIEW		
UPC Code	037332248671	
Technology	USB 3.x	
PHYSICAL		
Color	Black	
Material of Construction	PVC	
Shipping Dimensions (hwd / in.)	5.00 x 4.00 x 0.50	
Unit Dimensions (hwd / in.)	0.640 x 0.690 x 1.000	



Unit Dimensions (hwd / cm)	1.63 x 1.74 x 2.54	
Unit Dimensions (hwd / mm)	16.3 x 17.4 x 25.4	
Unit Packaging Type	Polybag	
ENVIRONMENTAL		
Operating Temperature Range	32 to 122 F (0 to 50 C)	
Storage Temperature Range	-4 to 140 F (-20 to 60 C)	
Relative Humidity	10% to 90%, Non-Condensing	
CONNECTIONS		
Side A - Connector 1	USB 3.0 A (MALE)	
Side B - Connector 1	USB 3.0 A (FEMALE)	
Connector Plating	Nickel	
Contact Plating	Gold	
FEATURES & SPECIFICATIONS		
USB Specification	USB 3.0 (up to 5 Gbps)	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.