TRIPP-LITE

USB 3.2 Gen 2 Active Extension Cable - USB-C to USB-A (M/F), 10 Gbps, Data Only, 5 m (16.4 ft.)

MODEL NUMBER: U330-05M-C2A-G2





Active 16 ft. extension cord increases the distance between two USB devices, including MacBooks and Windows laptops, without signal loss.

Features

USB Extension Cable Connects Computers, Printers, Modems and Other USB Equipment

This USB-C to USB-A Active Extension Cable (M/F) attaches to your current USB 3.2 Gen 2 cable to extend it by five meters (16.4 feet). It connects your MacBook Pro, Windows laptop, Chromebook or other compatible USB-C device to a USB-A webcam, keyboard, printer, portable hard drive, patch panel or other peripheral. The extra length allows you greater flexibility in placing equipment where most needed.

Built-In Signal Booster for Peak Performance

Just connect the active cable's USB-C plug to your computer's USB-C port and the USB-A female connector to a USB device cable to extend your total connection beyond USB's natural five-meter limit. The bus-powered signal booster ensures USB 3.2 Gen 2 data transfer speeds up to 10 Gbps, twice as fast as USB 3.2 Gen 1, with no signal loss. The cable is backward compatible with previous USB generations, so you can use it with legacy equipment.

900mA of Proper Power to Keep Devices Functioning

The U330-05M-C2A-G2 works with standard USB 3.2 Gen 2 cables and provides up to 900mA of power to a connected device.

Specifications

OVERVIEW	
UPC Code	037332268686
Technology	USB 3.x; USB
USB Cable Type	Active
INPUT	

Highlights

- Adds 5 meters to your existing USB connection to provide flexibility in placing devices
- Connects existing USB-A peripherals to newer laptops or tablets with USB-C ports
- Supports USB 3.2 Gen 2 speeds up to 10 Gbps to ensure fast data transfers
- Provides up to 900mA of power to connected device without need for external power
- Plug-and-play operation with no software required for easy, immediate installation

System Requirements

USB 3.2 Gen 2 computer port and USB 3.2 Gen 2 connected device required to meet USB 3.2 Gen 2 speeds

Package Includes

U330-05M-C2A-G2 USB-C Active Extension Cable, USB-C to USB-A (M/F), 5 m (16.4 ft.)

TRIPP-LITE

Bus Powered	Yes	
2.010.000		
POWER	1	
USB Power Delivery (PD) Charging Support	No	
PHYSICAL		
Material of Construction	TPE + ABS	
Cable Jacket Color	Black	
Cable Jacket Material	TPE	
Cable Outer Diameter (OD)	4.8MM	
Cable Length (ft.)	16.4	
Cable Length (m)	5.00	
Unit Packaging Type	Polybag	
Unit Weight (lbs.)	0.51	
Unit Weight (kg)	0.23	
ENVIRONMENTAL		
Operating Temperature Range	32 to 113 F (0 to 45 C)	
Storage Temperature Range	14 to 158 F (-10 to 70 C)	
Operating Humidity Range	10% TO 85% RH, Non-Condensing	
Storage Humidity Range	5% TO 90% RH, Non-Condensing	
Power Provided to Connected Device(s)	900mA	
CONNECTIONS		
Side A - Connector 1	USB C (MALE)	
Side B - Connector 1	USB A (FEMALE)	
Connector Plating	Nickel	
Contact Plating	Gold; Nickel	
FEATURES & SPECIFICATIONS		
USB Specification	USB 3.2 Gen 2 (Up to 10 Gbps)	
Driver Required	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		



1000 Eaton Boulevard Cleveland, OH 44122 United States

Product Warranty Period (Worldwide)

3-year limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.