

USB-C Dock, Dual Display - 4K 60 Hz HDMI, USB 3.2 Gen 1, USB-A Hub, GbE, Memory Card, 100W PD Charging, Gray

MODEL NUMBER: U442-DOCK8G-GG



USB-C docking station with PD Charging connects 2 HDMI displays, USB-A peripherals and Ethernet to your Chromebook, Windows laptop or tablet.

Features

USB-C Docking Station Turns Your Laptop into a Workstation

This USB-C dock with PD Charging expands the potential of your Windows laptop, Chromebook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for transmitting 4K video and digital audio to two large displays, adding a thumb drive and other USB peripherals, connecting to a wired Gigabit Ethernet network, and powering and charging a PD Charging-compliant mobile device, all at the same time.

Supports USB-C DisplayPort Alternate Mode for Converting Audio/Video Signals

By connecting the built-in USB-C cable to a source device that supports USB DisplayPort (DP) Alt Mode, you can output 4K video and digital audio to an HDMI monitor, television or projector without installing special software drivers.

Transmits 4K Video to 2 HDMI Displays Simultaneously

Two HDMI outputs each support 4K video resolutions up to 3840 x 2160 at 60 Hz with multi-channel sound, 36-bit Deep Color and 4:4:4 chroma subsampling. You can display the image from the host computer on both monitors, extend your host desktop across both with different windows open on each, or combine both into one large display as a video wall. Connect both monitors in Extended (4K at 30 Hz under MST/Windows) or Mirror (4K at 60 Hz under SST/Mac) mode. **Note:** When connecting a DP 1.4 Alt Mode host, the maximum HDMI resolution is 4K at 60 Hz for one monitor and 4K at 30 Hz for two. When connecting a DP 1.2 Alt Mode host, the maximum HDMI resolution is 4K at 30 Hz for one monitor and 1080p at 60 Hz for two, due to bandwidth limitation.

USB Ports Connect Keyboards, Thumb Drives and Other Peripherals

Two USB-A hub ports accept USB peripherals, such as flash drives, mice, keyboards and printers. They support fast USB 3.2 Gen 1 data transfer rates up to 5 Gbps and are backward compatible with earlier USB generations. One dedicated port also supports 5V 1.5A (7.5W) of charging power dedicated to fast-charging your mobile device. **Note:** Host must support USB OTG (USB On-the-Go).

PD Charging Port Charges the Connected Notebook, Tablet or Other Device

The USB-C port supports Power Delivery (PD) 3.0 charging of the connected PD Charging-compliant device. Connect the device's AC wall charger to the USB-C PD port, which supports power input up to

Highlights

Converts audio/video signals from sources supporting USB-C DisplayPort Alt Mode Supports UHD resolutions up to 4K @ 60 Hz (4:4:4) for crystal-clear video Power Delivery port supports 20V 5A (100W) power output for charging host device USB-A and memory card ports allow connection of flash drives and other peripherals Connects you to a wired Gigabit Ethernet network when Wi-Fi is unavailable

Applications

- Play 4K video from your laptop or PC on 2 HDMI displays
- Extend or mirror your desktop image across multiple displays at the same time
- Transfer data between your host computer and a USB-enabled thumb drive or external hard drive
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Access a wired Gigabit Ethernet network in a location with no or spotty Wi-Fi

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device(s) with HDMI input
- Multi-Stream Transport (MST) required to achieve extended dual displays; typically, Windows systems support MST
- Single-Stream Transport (SST) required to achieve mirrored dual displays; typically, Mac systems support SST

Package Includes

- U442-DOCK8G-GG USB-C Dock, Dual Display, Gray
- Owner's manual

20V 5A (100W). **Note:** 15W is dedicated to USB ports with remaining 85W available for PD Charging. This port does not support Quick Charge (QC).

Accesses a Wired Gigabit Ethernet Network

The RJ45 port offers access to a Gigabit Ethernet network when Wi-Fi is unavailable or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

Allows External Memory Access

The memory card slots support Micro SD and SD/MMC cards for transferring data to and from your connected computer, laptop or tablet. Both card slots can be used at the same time.

Built-In USB-C Cable Attaches in Either Direction

Unlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for an instant connection every time.

Ready to Use Right from the Package, So You Can Plug and Play Immediately

The plug-and-play USB-C dock is specifically designed for use with Windows laptops, Chromebooks and other devices equipped with a USB-C or Thunderbolt 3 port. It requires no extra software to be downloaded or installed and no external power. It fits into a purse, backpack or laptop bag for multiport convenience wherever you go.

Specifications

OVERVIEW	
UPC Code	037332261298
Product Type	Docking Station
Technology	HDMI; USB 3.x
Host Connector	USB C (MALE)
VIDEO	
Number of Monitors Supported	2
Video Ports	(2) HDMI (FEMALE)
Video Ports Details	HDMI 2.0; HDCP 1.4; HDCP 2.2
Resolutions Supported	3840 x 2160 @60Hz (Single)3840 x 2160 @30Hz (Dual Extended)
Max Supported Video Resolution	3840 x 2160 @60Hz (Single); 3840 x 2160 @30Hz (Dual Extended)
Extended Mode	Yes
Extended Mode Details	Dual 3840x2160 @ 30 Hz under MST mode (Windows System) Extended
Mirror Mode	Yes
Mirror Mode Details	Dual 3840*2160@60Hz under SST mode (Mac System) Mirrored
Max Supported Color Depth	36-bit Deep Color
HDR Support	No
Chroma Sub Sampling	4:2:2; 4:4:4

DATA	
Data Ports	(2) USB A (FEMALE)
Data Ports Details	(2) USB-A - USB 3.2 Gen 1 (5 Gbps)
NETWORK	
Network Ports	RJ45 (FEMALE)
STORAGE	
Card Slots	MICRO SD (FEMALE); SD (FEMALE)
INPUT	
Built-In Cable Length (ft.)	0.4
Built-In Cable Length (m)	0.12
Built-In Cable Length (in.)	4.72
Bus Powered	Yes
BATTERY	
Battery Charging (5V/1.5A Port)	Yes
POWER	
Power Consumption (Watts)	15.00
USB Power Delivery (PD) Charging Support	Yes
USB Power Delivery (PD) Charging Specification	100W; 3.0
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	RJ45 Port: White (Connection), Orange (Activity)
CHARGING	
Total Charging Watts	100
Charging Ports	USB-A: 5V 1.5A (7.5W) ; USB-C: 85W Power Delivery (PD 3.0)
Charging Ports / Amps	1.5A; 5A
PHYSICAL	
Color	Black; Gray
Material of Construction	Aluminum, ABS
Cable Jacket Material	TPE
Cable Jacket Rating	VW-1

Shipping Weight (lbs.)	0.22
Unit Dimensions (hwd / in.)	4.330 x 0.450 x 2.320
Unit Packaging Type	Box
Unit Weight (lbs.)	0.2
Unit Weight (kg)	0.09
ENVIRONMENTAL	
Operating Temperature Range	32 to 113 F (0 to 45 C)
Storage Temperature Range	14 to 158 F (-10 to 70 C)
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	5% to 90% RH, Non-Condensing
Power Provided to Connected Device(s)	USB-A: 5V/1.5A (7.5W), USB-C: 20V/5A (100W)
COMMUNICATIONS	
Network Compatibility	1 Gbps (Gigabit)
CONNECTIONS	
Number of Ports	8
Dock Connectors	(2) USB-A 3.0, USB-C PD Charging, RJ45, (2)HDMI, MICRO SD, SD
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	(2) HDMI (FEMALE)
Side B - Connector 2	(2) USB A (FEMALE)
Side B - Connector 3	USB C (FEMALE)
Side B - Connector 4	MICRO SD (FEMALE); SD (FEMALE)
Side B - Connector 5	RJ45 (FEMALE)
Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
Over Current Protection	Y
Displayport Specification	1.2; 1.4
HDCP Specification	1.4; 2.2
USB Hub Ports	Yes
Number of USB Hub Ports	2
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps)
Driver Required	No
Recommended Category Cable	Cat5e/6/6a Cables

UASP Support	No
Auto MDIX Support	No
Full Duplex Support	Yes
Suspend Mode Support	Yes
Remote Wakeup Support	Yes
Quick Charge Compliant	No
SD Card Specification	SD; Micro SD
Ethernet Support	Yes
STANDARDS & COMPLIANCE	
TAA Compliant Option	N
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty