BASIC PACKAGING UNIT

■ ORDERING INFORMATION

Please note the order quantity must be in multiples of the minimum quantity.

Type • Series		Capacitance (µF)	Bulk minimum quantity	Taping minimum quantity (Ammo-pack)
QXK-(zh)	0.047 to 0.1			1,000
	250VDC	0.15 to 1.0	*	500
		1.5 to 3.3	-	
	400VDC	0.022 to 0.047		1,000
		0.068 to 0.22		500
		0.33		400
		0.47		300
		0.68 to 1.5		
		0.01 to 0.015		1,000
	630VDC	0.022 to 0.068	*	500
		0.1		400
		0.15 to 0.47		-
	250VDC	0.01 to 0.33		1,000
		0.47 to 1.0		500
		1.5	. *	400
QXK		2.2 to 10.0		
	400VDC	0.01 to 0.1		1,000
		0.15 to 0.22		500
				400
		0.68 to 2.2		1,000
	630VDC	0.01 to 0.047		1,000
		0.068 to 0.15	. *	500
		0.22		300
		0.33 to 2.2		
	250VDC	0.047 to 0.068	*	1,000
QXP		0.1 to 0.15		500
		0.22 to 0.33		400
		0.47 to 0.68		300
		1.0 to 3.3		_
	400VDC	0.022 to 0.033	*	1,000
		0.047 to 0.068		500
		0.1 to 0.15		400
		0.22 to 0.33		300
		0.47 to 1.5		
	630VDC	0.01 to 0.015	*	1,000
		0.022 to 0.068		500
		0.1		400
		0.15		300
		0.22 to 0.68		
	800VDC	0.01	*	1,000
		0.015 to 0.033		500
		0.047 to 0.068		400
		0.1		300
		0.15 to 0.47		
QXT	400, 630VDC	0.13 to 0.47 0.0068 to 0.1	*	<u>–</u>
QXL	125, 250VAC	0.0068 to 0.1	* *	*
QAK, QAP	250, 400, 630VDC	0.1 to 10.0	*	
QYX	50VDC	0.001 to 0.022	1,000	2,000
		0.033 to 0.22		
		0.33 to 0.47		1,000
	100VDC	0.33 to 0.47 0.001 to 0.022	1,000	<u> </u>
		0.001 to 0.022		
		0.000 10 0.1		1,000
		0.45 1: 0.47		
EEC		0.15 to 0.47 Whole series	100	<u> </u>

[%] Please refer to "Taped capacitors for automatic insertion systems" in the Guidelines for Plastic Film Capacitors.