

MODEL:
Switched PDU



MODEL NUMBER:
OSP-V-20-11-16-N1



Input (left)

Features

| | |
|------------------|---|
| Current Meter | Digital True RMS Current Meter |
| Power Monitor | Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software |
| Protocols | http, https, SNMP, DHCP, UDP |
| Outlet Control | Individual Outlet Control |
| Power Delay | Power On/Off Sequence can be Defined |
| Alarm Thresholds | User-Defined Alarm Thresholds for Warning and Overload |
| Event Alert | Email, Trap, Audible Alarm |

Specification:

| General | Communication | Operation |
|--|---|--|
| Output: (16) NEMA 5-20/15R Input: (1) IEC320 C20 Inlet; Enclosed IEC320 C19 to NEMA 5-20P Power Cord 3 Meters long Protection (1) 20 Amp Circuit Breaker | SSL Indication (1) Yellow LED DHCP Indication (1) Green LED Output Status (16) Red LED Network (1) RJ45 for Ethernet Current Meter 3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20A Resolution: 0.1A Precision: +/-2%+/-0.1 Amp | Nominal Voltage 115V Voltage 100V~ 127V full range Frequency 50/60HZ full range Max. Output Current 20 Amp (UL derated 1 Amp) Temperature 0 ~ 40 Celsius degree Humidity 0% ~ 90% Size 56 x 1245 x 44 mm Weight 4 kg |

Regulatory Approvals:

UL 60950-1, UL Listed, CSA, cUL Listed, CB by UL
 CE, EN 55022 Class A, EN 5024, EN 61000-3-2, EN 61000-3-3, C-Tick AS/NZS CISPR 22: 2006
 FCC Part 15 Class A, ICES-003