8P1P YYY 200 GRF 01 **SERIES** - 1 = GOLD FLASH 14.00 [0.551] **ROHS COMPLIANT** NUT "B" COLOR # OF POSITIONS G = GREY (Ex. 002) **SÈE CHART A** 2 = FEMALESOLDER CUP (PANEL MOUNT) PLASTIC SHELL [0.955] 24.25 [0.797] 20.25 [0.669] [0.488] 12.40 0.157 4.00 0.315

CHARACTERISTICS MATERIALS

HOUSING: ABS+PC
HOUSING COLOR: GREY
NUT A: BRASS

NUT A PLATING : NICKEL CONTACTS : COPPER ALLOY

CONTACT PLATING: 7µ" GOLD PLATED OVER 196µ" NICKEL MIN.

INSULATOR: PPS (HIGH TEMPERATURE)


MECHANICAL

DURABILITY: 2000 CYCLES

OPERATING TEMP. RANGE: -20° C ~ +120° C PROCESS TEMPERATURE: 260°C FOR 5 SECONDS

MAX. TORQUE VALUE: 0.7 Nm [6.19 IN/lbs]

IP RATING: 50



PANEL CUTOUT

TOLERANCE = +0.10, -0.0 [+0.004, -0.00]



14 POSITION 26 AWG MAX. 2 AMP MAX. PIN Ø = 0.50 [0.020]

CONTACT
RESISTANCE = 10 m Ω TEST VOLTAGE = 600V
WORKING VOLTAGE = 200V

CHART A

= KEY LOCATION

8.00

MAX. PANEL THICKNESS

VIEW FROM TERMINATION END



2 POSITION 22 AWG MAX. 10 AMP MAX. PIN Ø = 1.30 [0.051]

CONTACT
RESISTANCE = 5 mΩ
TEST VOLTAGE = 1200V
WORKING VOLTAGE = 400V



3 POSITION 22 AWG MAX. 10 AMP MAX. PIN Ø = 1.30 [0.051]

CONTACT RESISTANCE = 5 mΩ TEST VOLTAGE = 1200V WORKING VOLTAGE = 400V



4 POSITION 22 AWG MAX. 8 AMP MAX. PIN Ø = 0.90 [0.035]

CONTACT RESISTANCE = 6 mΩ TEST VOLTAGE = 1200V WORKING VOLTAGE = 400V



5 POSITION 22 AWG MAX. 7 AMP MAX. PIN Ø = 0.90 [0.035]

CONTACT
RESISTANCE = 6 mΩ
TEST VOLTAGE = 1050V
WORKING VOLTAGE = 350V



6 POSITION 24 AWG MAX. 6 AMP MAX. PIN Ø = 0.70 [0.028]

CONTACT
RESISTANCE = 7.5 mΩ
TEST VOLTAGE = 1050V
WORKING VOLTAGE = 350V



7 POSITION 24 AWG MAX. 5 AMP MAX. PIN Ø = 0.70 [0.028]

CONTACT RESISTANCE = $7.5 \text{ m}\Omega$ TEST VOLTAGE = 1050 VWORKING VOLTAGE = 350 V



8 POSITION 24 AWG MAX. 5 AMP MAX. PIN Ø = 0.70 [0.028]

CONTACT
RESISTANCE = 7.5 mΩ
TEST VOLTAGE = 1050V
WORKING VOLTAGE = 350V



9 POSITION 26 AWG MAX. 3 AMP MAX. PIN Ø = 0.50 [0.020]

CONTACT RESISTANCE = 10 mΩ TEST VOLTAGE = 850V WORKING VOLTAGE = 280V



10 POSITION 26 AWG MAX. 3 AMP MAX. PIN Ø = 0.50 [0.020]

CONTACT RESISTANCE = 10 mΩ TEST VOLTAGE = 850V WORKING VOLTAGE = 280V

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NOTCOMP AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

DRAWN: M. SIGMON	DATE: 10-04-16	SCALE: N.T.S.	SHEET 1	OF 1		REV:
			DWG NO.	8P1PYYY200GRF01		