


RJI RJ45 6-port jack Cat.5 THT angled



•	
Part number	09 45 551 1126
Specification	RJI RJ45 6-port jack Cat.5 THT angled
HARTING eCatalogue	https://b2b.harting.com/09455511126

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	HARTING RJ Industrial [®]
Element	Female
Specification	RJ45 Angled
	6 ports

Version

Termination method	Wave soldering termination
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8

Technical characteristics

Rated current	1.5 A
Rated voltage	125 V
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s
Limiting temperature	-40 +85 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP20

Page 1 / 2 | Creation date 2022-09-14 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 DUXR2.E254191 CSA-C22.2 No. 182.4, No. 233-09 DUXR8.E254191

Commercial data

Packaging size	40
Net weight	28.82 g
Country of origin	Taiwan
European customs tariff number	85366990
GTIN	5713140061606
eCl@ss	27460201 PCB connector (board connector)