

Specification Sheet

Part Number: 111-12302

Wide strap is designed to minimize pinching of soft hoses and convoluted tubing.

Low-profile head with clamping rails provide compact bundling with a full circumferential compression around bundles.

Wider and thinner strap design increases flexibility, provides low insertion and minimizes pinching of bundles.

Bent tail allows for quick insertion into head or mounts.



Wide Strap Cable Tie, 15.1"L, 0.375 - 4.125" Bndl Dia, 120lb Tens Stngth, PA66HIRHSUV, Black, 300/pkg

Article Number 111-12302

Type WSR

Color Black (BK)

Quantity Per bag

Product Description The Heavy Duty Wide-Strap Cable Tie was designed to minimize the

pinching of soft bundles and the potential of lateral movement along the bundle. The low-profile head and underside clamping rails increase the grip around the bundle and provide a better fit than traditional cable ties. These are used primarily in the trucking and heavy equipment industries, but can be used in a wide variety of

applications where strength is needed.

Short Description	Wide Strap Cable Tie, 15.1"L, 0.375 - 4.125" Bndl Dia, 120lb Tens Stngth, PA66HIRHSUV, Black, 300/pkg			
Global Part Name	WSR-PA66HIRHSUV-BK			
Minimum Tensile Strength (Imperial)	120.0			
Minimum Tensile Strength (Metric)	535.0			
Length L (Imperial)	15.1			
Length L (Metric)	383.5			
Identification Plate Position	none			
Releasable Closure	No			
Tie Closure	plastic pawl			
Variant	Inside Serrated			
Width W (Imperial)	0.5			

12.7

0.38

9.5

4.13

Width W (Metric)

Bundle Diameter Min (Imperial)

Bundle Diameter Min (Metric)

Bundle Diameter Max (Imperial)

Bundle Diameter Max (Metric)	105.0
Thickness T (Imperial)	0.055
Thickness T (Metric)	1.4
Cable Tie Head Length (Imperial)	0.393
Cable Tie Head Width (Imperial)	0.78
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	300
Package Quantity (Metric)	300

Customs Number	3926	909988		
© 2023 HellermannTyton. All Rights Resonant		RoHS/WEEE Compliance	Disclaimer	Terms and Conditions