

Specification Sheet

Part Number: 115-00145

Provides dual separation between bundles to prevent chafing and abrasion.

150lb tensile strength ensures enough strength for heavy duty applications.

Straps are releasable for increased serviceability.



Dual Clamp Tie w/Neoprene Sleevings, 0.25" Stud Dia, 2.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black, 500/pkg

Article Number 115-00145

Type DCT11SLVH1

Color Black (BK)

Quantity Per bag

Product Description Dual-Clamp Ties are designed to provide parallel separation between hoses, wires, cables, and tubing to protect them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of trucks, trailers, and heavy-duty equipment. The unique one-piece design features the dual head centered on the strap.

Short Description Dual Clamp Tie w/Neoprene Sleevings, 0.25" Stud Dia, 2.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black, 500/pkg

Global Part Name

DCT11SLVH1-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 150.0

Minimum Tensile Strength (Metric) 667.0

Length L (Imperial) 19.25

Length L (Metric) 489.0

Fixation Method Weld Stud Fixing

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.504

Width W (Metric) 12.8

Bundle Diameter Min (Imperial) 0.20

Bundle Diameter Min (Metric) 6.4

Bundle Diameter Max (Imperial) 2.28

Bundle Diameter Max (Metric) 58.0

Height H (Imperial)	0.75
Height H (Metric)	19.1
Mounting Hole Diameter D (Imperial)	0.20
Mounting Hole Diameter D (Metric)	6.2 mm
Mounting Hole Diameter D Min (Imperial)	0.20
Mounting Hole Diameter D Max (Imperial)	0.20
Mounting Hole Diameter D Max (Metric)	6.2
Stud Diameter (Metric)	6.35 mm
Stud Diameter (Imperial)	0.25
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Reach Compliant (Article 33)	No
ROHS Compliant	Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988