

Specification Sheet

Part Number: DCT90HIRK2

Provides dual separation between bundles to prevent chafing and abrasion.

150lb. tensile strength ensures enough strength for heavy duty applications.

Straps are releasable for increased serviceability.



Dual Clamp Tie, 0.25" Stud Dia, 1.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black 50/pkg

Article Number 115-30900

Type DCT9

Color Black (BK)

Quantity Per bag

Product Description Dual-Clamp Ties are designed to provide parallel separation between hoses, wires, cables, and tubing to protect them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of trucks, trailers, and heavy-duty equipment. The unique one-piece design features the dual head centered on the strap.

Short Description Dual Clamp Tie, 0.25" Stud Dia, 1.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black 50/pkg

Global Part Name DCT9-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 150.0

Minimum Tensile Strength (Metric) 667.0

Length L (Imperial) 13.0

Length L (Metric) 331.0

Fixation Method Weld Stud Fixing

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.504

Width W (Metric) 12.8

Bundle Diameter Min (Imperial) 0.25

Bundle Diameter Min (Metric) 6.4

Bundle Diameter Max (Imperial) 1.3

Bundle Diameter Max (Metric) 33.0

Height H (Imperial)	0.8
Height H (Metric)	20.32
Stud Diameter (Metric)	M6
Stud Diameter (Imperial)	1/4
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)