

Specification Sheet

Part Number: 151-01612

Easy to install, remove and reposition with just a quarter-turn – no tools necessary.

Multi-directional cable tie slot allows for routing a bundle parallel to or perpendicular to the frame.

Low profile is ideal for cramped spaces.

Designed to fit an 80/20 profile with a T-slot of 8 mm (0.32") and external dimensions of 40 mm (1.5").



Aluminum Frame Mount for 40mm or 1.5" Frame, 4.0 - 4.8mm Panel Thickness, PA66, White, 100/bag

Article Number 151-01612

Type AFLM40-1

Color Natural (NA)

Quantity Per bag

Product Description Aluminum frame mounts can be used with 20, 30 or 40 mm square frames from the major aluminum frame manufacturers. As there is no need to screw them in place, these mounts offer maximum ease of use and fast installation.

Short Description Aluminum Frame Mount for 40mm or 1.5" Frame, 4.0 - 4.8mm Panel Thickness, PA66, White, 100/bag

Global Part Name AFLM40-1-PA66-NA

Length L (Imperial) 1.10

Length L (Metric) 28.0

Width W (Imperial) 0.83

Width W (Metric) 21

Cable Ties T18 - T50

Height H (Imperial) 0.80

Height H (Metric) 20.2

Cable Tie Width Max (Imperial) 0.49

Cable Tie Width Max (Metric) 12.5

Panel Thickness Min (Imperial) 0.16

Panel Thickness Max (Imperial) 0.19

Panel Thickness Min (Metric) 4.0

Panel Thickness Max (Metric) 4.8

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988