

Specification Sheet

Part Number: 596-00846

Pre-Printed Vinyl Solar Labels are made with UV-stable inks and

materials for durability and weather resistance.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC® & IFC standards for printed text, character height, color and

outdoor UV stability to pass inspections.

AWARNING
INVERTER OUTPUT
CONNECTION. DO
NOT RELOCATE
THIS OVERCURRENT
DEVICE.

Pre-printed labels offer significant time and cost savings over high-priced plastic engraved phenolic placards and the lead time of purchased markers.

Solar Label, WARNING INVERTER OUTPUT...OVERCURRENT DEVICE, 2.0" x 1.25", VL, Orange, 50/roll

Article Number 596-00846

Type IOCOD14

Color Orange (OG)

Quantity Per roll

Product Description	HellermannTyton pre-printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Short Description	Solar Label, WARNING INVERTER OUTPUTOVERCURRENT DEVICE, 2.0" x 1.25", VL, Orange, 50/roll
Global Part Name	IOCOD14-443/281-OG
Length L (Imperial)	1.25
Length L (Metric)	31.75
Width W (Imperial)	2.0
Width W (Metric)	50.8
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	1.25

31.75

Height H (Metric)

Material	Type 443/281, UV-stabilized flexible white vinyl with clear polyester laminate (443/281)
Material Shortcut	443/281
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	Yes
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33) ROHS Compliant	Yes
Certification/Specification	UL 969 NEC2014
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50

3919102055

Customs Number

Labels per Column	1
Labels per Row	1

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions