CHIPQUIK®

Thermoset Chip Glue

Safety Data Sheet (SDS)

www.chipquik.com

To comply with European CLP Regulation 1272/2008, US 29CFR 1910.1200 OSHA's Hazard Communication Standard, and Australian NOHSC: 1008 [2004] and ADG Code 7.4

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Chip Quik Series: AD1, AD6

SYNONYMS:

PART NUMBERS: AD1-10S, AD1-30S, AD1-200S, AD6-5S, AD6-10S, AD6-30S, AD6-360S

MANUFACTURER: Chip Quik Inc.

ADDRESS: 931-3909 Witmer Rd., Niagara Falls, NY 14305 (USA)

3rd Floor, 207 Regent Street, London W1B 3HH (UK and EU) 8-1500 Sandhill Dr., Ancaster, ON L9G 4V5 (Canada)

42A Crimea Street, C/O A03886, Parramatta, NSW, 2150 (Australia)

PHONE: (508) 477-2264

EMERGENCY PHONE: (800) 424-9300 (USA and Canada 24/7 CHEMTREC)

+44 20 3868 7152 (UK and EU 24/7) +61 2 8607 7057 (Australia 24/7)

REVISION DATE: 2022/04/06

REVISION NUMBER: 1.6

REVISED BY: Chip Quik Product Safety

PRODUCT USE: Bonding chips in production and repair of circuit boards.

2. HAZARD IDENTIFICATION

Classified in accordance with European CLP Regulation 1272/2008

Acute Toxicity 4
Skin Irritant 2
Skin Sensitization 1

CHEMICAL NAME: NA
CHEMICAL FAMILY: Mixture
CHEMICAL FORMULA: Proprietary

ROUTES OF ENTRY: Inhalation, Ingestion, Skin/Eye Contact

TARGET ORGANS: NA

GHS/CLP:



Signal Word: Warning

GHS/CLP LABEL ELEMENTS:

Hazard statement(s)

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Precautionary statement(s)

P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P233 Keep container tightly closed.

P260 Do not breathe dust/fume/gas/mist/vapor/spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash hands thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P271 Use in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 In case of inadequate ventilation wear respiratory protection.

P301/P330/P331/P310 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER/Doctor.

P303/P361/P352/P333/P313 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with soap & water. Get medical advice/attention if

skin irritation or rash occurs or if you feel unwell.

P304/P340/312 IF INHALED: Remove victim to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if

you feel unwell.

P305/P351/338/P310 F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call POISON CENTER/Doctor.

P308/P313 IF EXPOSED OR CONCERNED: Get medical advice/attention.

P342/P311 IF EXPERIENCING RESPIRATORY SYMPTOMS: Call POISON CENTER/Doctor.

P362 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P402/P404 Store in a dry place. Store in a closed container.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: May cause moderate irritation. Do not allow material to come in contact with eyes.

SKIN CONTACT: May cause moderate skin irritation.

INHALATION: May cause irritation to the respiratory tract.

INGESTION: Harmful if swallowed. May cause irritation to the mouth, throat, and stomach. May cause abdominal discomfort, nausea,

vomiting, and/or diarrhea.

CHRONIC: Not established.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: Diseases of the blood-forming organs, kidneys, nervous and possibly reproductive systems. Occupational Asthma.

SECTION 2 NOTES:

Chip Quik Inc. does not recommend, manufacture, market, or endorse any of its products for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Classified in accordance with European CLP Regulation 1272/2008

Hazardous Ingredients (1)	C.A.S. Number	Weight Percent	OSHA PEL	ACGIH TLV TWA	LD 50 Ingested	LD 50 Inhaled
			mg/m ³	mg/m ³	g/Kg	g/m ³
Silicon Dioxide	14808-60-7	40	NE	NE	NE	NE
Epoxy Resin	38891-59-7	59	NE	NE	NE	NE

Non-Hazardous Ingredients	C.A.S. Number	Weight Percent	OSHA PEL mg/m ³	ACGIH TLV TWA mg/m ³	LD 50 Ingested g/Kg	LD 50 Inhaled g/m ³
Color	NA	1	NE	NE	NE	NE

SECTION 3 NOTES:

(1) Per 29 CFR 1910 the mixture has not been tested as a whole. All hazardous components, which comprise 1% of the mixture (0.1% carcinogenic), are listed. Percentages of individual components are not listed as this information is considered a trade secret.

4. FIRST-AID MEASURES

EYES: Flush with plenty of water, contact a physician. If contact lenses can be removed easily, flush eyes without contact lenses.

SKIN: Wash affected area with plenty of warm, soapy water. If irritation persists, seek medical attention.

INGESTION: Call a physician or Poison Control Center immediately. Do not induce vomiting.

INHALATION: Remove to fresh air. If not breathing, seek immediate medical attention.

5. FIREFIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam

SPECIAL FIRE FIGHTING PROCEDURES: Do not use water. Use NIOSH-approved self-contained Breathing Apparatus and full protective clothing if

involved in a fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: This product does not present any unusual fire and explosion hazards.

6. ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: If material spills or leaks use a spatula to collect and place it in a plastic or glass jar. Remove traces of residue using cloth rags or paper towels moistened with Isopropyl Alcohol. Exposure to spilled material may be irritating. Follow on-site personal protective equipment recommendations.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Collect spillage.

SECTION 6 NOTES:

See Sections 2, 4, and 7 for additional information.

7. HANDLING AND STORAGE

HANDLING/STORAGE: Keep containers tightly closed when not in use. Use care to avoid spills. Avoid inhalation of fumes or dust. Avoid contact with eyes, skin, and clothing. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Wear appropriate personal protective equipment when working with or handling. Always wash hands thoroughly after handling this product. Dispose of following Federal, State/Provincial, and Local regulations.

OTHER PRECAUTIONS: Empty containers may retain product residues in vapor, liquid, and/or solid form. All labeled hazard precautions should be observed.

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in work areas. Always wash hands after handling material and before applying or using cosmetics/food/drink/tobacco.

SECTION 7 NOTES:

Keep out of reach of children. Not for internal consumption.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limit Values:

Rosin flux fumes (as total resin acids)

MEL: 0.05 mg/m³ 8h TWA. MEL: 0.15 mg/m³ 15 min.

Extraction is necessary to remove fumes evolved during reflow.

Also see section 3.

ENGINEERING CONTROLS: Use only with production equipment designed for use with thermoset adhesives.

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLVs.

RESPIRATORY PROTECTION: Use with adequate ventilation.

EYE PROTECTION: Use with appropriate safety glasses.

SKIN PROTECTION: Protective gloves.

PROTECTIVE CLOTHING OR EQUIPMENT: Work clothes should be worn and laundered in accordance with current OSHA Lead (Pb) standards.

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in areas where solder products may be used. Always wash hands after handling soldering products and before applying or using cosmetics/food/drink/tobacco.

OTHER: Maintain eye wash stations in work areas. Avoid the use of contact lenses in high fume areas. Clean protective equipment regularly. Clean up spills immediately.

9. PHYSICAL AND CHEMICAL PROPERTIES

Red liquid APPEARANCE: ODOR: Mild odor **ODOR THRESHOLD:** NF pH as SUPPLIED: N/A NE **MELTING POINT:** FREEZING POINT: ΝE **INITIAL BOILING POINT:** NE **BOILING RANGE:** NE FLASH POINT: NF **EVAPORATION RATE:** NE FLAMMABILITY (solid): ΝE **UPPER/LOWER FLAMMABILITY:** ΝE **UPPER/LOWER EXPLOSIVE LIMITS:** NF VAPOR PRESSURE (mmHg): N/A **VAPOR DENSITY (AIR = 1):** N/A **RELATIVE DENSITY:** NE SOLUBILITY IN WATER: Partially PARTITION COEFFICIENT (n-octanol/water): NE **AUTOIGNITION TEMPERATURE:** NE **DECOMPOSITION TEMPERATURE:** ΝE VISCOSITY: N/A

10. STABILITY AND REACTIVITY

STABILITY: Stable CONDITIONS TO AVOID (STABILITY): NE

INCOMPATIBILITY (MATERIAL TO AVOID): Oxidizing materials, acids, hydrogen peroxide, bases

HAZARDOUS DECOMPOSITION/BY-PRODUCTS: Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.

POSSIBILITY OF HAZARDOUS REACTIONS:

11. TOXICOLOGICAL INFORMATION

INHALATION:

This product does not present a risk at ambient temperatures. The resin fumes evolved during reflow will irritate the nose, throat and lungs. Repeated or prolonged exposure to resin fumes may cause an allergic affect which may lead to occupational asthma.

NE

SKIN

Contact with resin fumes and resin residues may cause irritation and sensitization.

EYES:

Resin fumes may cause irritation.

ACUTE TOXICITY: Not available SKIN CORRISION/IRRITATION: Not available SERIOUS EYE DAMAGE/IRRITATION: Not available

RESPIRATORY OR SKIN SENSITIZATION: NE

GERM CELL MUTAGENICITY:

CARCINOGENICITY:

REPRODUCTIVE TOXICITY:

STOT-SINGLE EXPOSURE:

STOT-REPEATED EXPOSURE:

Not available
NE

ASPIRATION HAZARD: NE

12. ECOLOGICAL INFORMATION

TOXICITY: Not available

PERSISTENCE AND DEGRADIBILITY: NE

BIOACCUMULATIVE POTENTIAL: Not available MOBILITY IN SOIL: NE

RESULT OF PBT and vPvB ASSESSMENT: Not applicable

OTHER ADVERSE EFFECTS: NE

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Scrap and waste should be recycled or stored in a dry, sealed container for later disposal. Disposal must be in accordance with Federal, State/Provincial, and Local Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

UN Number:
UN Proper Shipping Name:
Packaging Group:
Environmental Hazards:
Not available
Not applicable
None

TRANSPORT HAZARD CLASSES:

US DOT Hazardous Material Classification:
Water Transportation:
Non-Hazardous
Non-Hazardous
Non-Hazardous
Non-Hazardous
Non-Hazardous
Not regulated
Not regulated
ADG Land Transportation
Not regulated
Not regulated

15. REGULATORY INFORMATION

All ingredients used to manufacture this product are listed on the EPA TSCA Inventory. Finished product is not listed on the EPA TSCA Inventory.

U.S. FEDERAL REGULATIONS:
STATE REGULATIONS:
INTERNATIONAL REGULATIONS:
AUSTRALIAN REGULATIONS:
Not regulated
Not regulated
Not regulated

16. OTHER INFORMATION

LEGEND:

ACGIH American Conference of Governmental Industrial Hygienists

ADG Australian Dangerous Goods Code

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS Australian Inventory of Chemical Substances

BCF Bioconcentration factor C.A.S. Chemical Abstract Service

CLP Classification, Labeling and Packaging

DOT Department of Transportation EC Effective Concentration

EPA Environmental Protection Agency

GHS Global Harmonized System

HMIS
IARC
International Agency for Research on Cancer
IATA
International Air Transport Association
IMDG
International Maritime Dangerous Goods Code

LC Lethal Concentration

LD Lethal Dose
NA Not available
NE Not established

NIOSH National Institute for Occupational Safety & Health

NOEC No observed effective concentration

NOHSC National Occupational Health and Safety Commission (Australia)

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit
Pow Octanol water partition coefficient

SDS Safety Data Sheet

STEL Short-Term Exposure Limit
STOT Specific target organ toxicity
TLV Threshold Limit Value
TSCA Toxic Substance Control Act
TWA: Time Weighted Average

US DOT: United States Department of Transportation

PREPARATION INFORMATION:

This update supersedes all previously released documents.

DISCLAIMER:

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to Chip Quik at the time of issue. No warranty, guarantee, or representation is made by Chip Quik nor does Chip Quik assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances. The data on this Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet as a source for hazard information.

Copyright © 1994-2022 Chip Quik® Inc.