CHIPQUIK®

Safety Data Sheet (SDS) www.chipquik.cc To comply with European CLP Regulation 1272/2008, US 29CFR 1910.1200 OSHA's Hazard Communication Standard, and Australian NOHSC: 1008 [2004] and ADG Code 7.4

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SYNONYMS:	Chip Quik Super Glue Series: SG1, SG2, SG3, SG4
PART NUMBERS:	SG1-0.5, SG1-1.0, SG2-0.5, SG2-1.0, SG3-0.5, SG3-1.0, SG4-1.0
MANUFACTURER: ADDRESS: PHONE:	Chip Quik Inc. 931-3909 Witmer Rd., Niagara Falls, NY 14305 (USA) 3rd Floor, 207 Regent Street, London W1B 3HH (UK and EU) 8-1500 Sandhill Dr., Ancaster, ON L9G 4V5 (Canada) 42A Crimea Street, C/O A03886, Parramatta, NSW, 2150 (Australia) (508) 477-2264
EMERGENCY PHONE:	(800) 424-9300 (USA and Canada 24/7 CHEMTREC) +44 20 3868 7152 (UK and EU 24/7) +61 2 8607 7057 (Australia 24/7)
REVISION DATE: REVISION NUMBER: REVISED BY:	2021/11/22 1.5 Chip Quik Product Safety

Rapidly bonding materials together.

2. HAZARD IDENTIFICATION

Classified in accordance with European CLP Regulation 1272/2008

CHEMICAL NAME:	Cyanoacrylat
Skin Irritant	2
Skins Sensitization	1
Eye Irritation	2
Acute Toxicity	4

CHEMICAL NAME:	Cyanoacrylate Ester
CHEMICAL FAMILY:	Mixture
CHEMICAL FORMULA:	Proprietary

NA

ROUTES OF ENTRY:

PRODUCT USE:

Inhalation, Ingestion, Skin/Eye Contact

TARGET ORGANS:

GHS/CLP:



Hazard statement(s)

GHS/CLP LABEL ELEMENTS:

EUH202	Contains cyanoacrylates.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
Precautionary statement(s)	
EUH202	Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P233	Keep container tightly closed.
P260	Do not breathe dust/fume/gas/mist/vapor/spray.
P262	Do not get in eyes, on skin, or on clothing.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink, or smoke when using this product.

www.chipquik.com

Super Glue

P271	Use in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	In case of inadequate ventilation wear respiratory protection.
P301/P330/P331/P310	IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER/Doctor.
P303/P361/P352/P333/P313	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with soap & water. Get medical advice/attention if skin irritation or rash occurs or if you feel unwell.
P304/P340/312	IF INHALED: Remove victim to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
P305/P351/338/P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call POISON CENTER/Doctor.
P308/P313	IF EXPOSED OR CONCERNED: Get medical advice/attention.
P342/P311	IF EXPERIENCING RESPIRATORY SYMPTOMS: Call POISON CENTER/Doctor.
P362	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P402/P404	Store in a dry place. Store in a closed container.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
POTENTIAL HEALTH EFFE	CTS:
EYE CONTACT:	Causes serious eye irritation. Do not allow material to come in contact with eyes.
SKIN CONTACT:	May cause moderate skin irritation.
INHALATION:	May cause irritation to the respiratory tract.
INGESTION:	Harmful if swallowed. May cause irritation to the mouth, throat, and stomach. May cause abdominal discomfort, nausea,
	vomiting, and/or diarrhea.
CHRONIC:	Not established.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: Persons suffering from allergic reactions to acrylates should avoid contact with this product. Occupational Asthma.

SECTION 2 NOTES:

Chip Quik Inc. does not recommend, manufacture, market, or endorse any of its products for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Classified in accordance with European CLP Regulation 1272/2008

Hazardous Ingredients (1)	C.A.S. Number	Weight Percent	OSHA PEL	ACGIH TLV TWA	LD 50 Ingested	LD 50 Inhaled
_		-	mg/m ³	mg/m ³	g/Kg	g/m ³
Ethyl Cyanoacrylate	7085-85-0	70-100	NE	NE	NE	NE
Poly Methyl Methacrylate	9011-14-7	0-30	NE	NE	NE	NE
Hydroquinone	123-31-9	0-0.5	NE	NE	NE	NE

SECTION 3 NOTES:

(1) Per 29 CFR 1910 the mixture has not been tested as a whole. All hazardous components, which comprise 1% of the mixture (0.1% carcinogenic), are listed. Percentages of individual components are not listed as this information is considered a trade secret.

4. FIRST-AID MEASURES

EYES: In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye should open without further action, typically in 1 to 4 days. There should be no residual damage. Do not try to open the eyes by manipulation. Contact a physician immediately.

SKIN: Wash affected area with plenty of warm, soapy water. Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water. If irritation persists, seek medical attention.

BURNS: Cyanoacrylates give off heat on solidification. In rare cases, a large drop will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of Cyanoacrylate is released.

INGESTION: Call a physician or Poison Control Center immediately. Do not induce vomiting. If lips are accidentally stuck together, apply lots of warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips with direct opposing action. It is almost impossible to swallow Cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in ½ to 2 days. In case a lump forms in the mouth, position the patient to prevent ingestion of the lump when it detaches.

INHALATION: Remove to fresh air. If not breathing, seek immediate medical attention.

5. FIREFIGHTING MEASURES

EXTINGUISHING MEDIA:	Dry chemical, foam	
SPECIAL FIRE FIGHTING PROCEDURES:	Do not use water. Use NIOSH-approved self-contained Breathing Apparatus and full protective clothing if involved in a fire.	
UNUSUAL FIRE AND EXPLOSION HAZARDS:	This product does not present any unusual fire and explosion hazards.	

6. ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: If material spills or leaks use cloth rags or paper towels to soak up. Exposure to spilled material may be irritating. Follow on-site personal protective equipment recommendations.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Collect spillage.

SECTION 6 NOTES:

See Sections 2, 4, and 7 for additional information.

7. HANDLING AND STORAGE

HANDLING/STORAGE: Keep containers tightly closed when not in use. Use care to avoid spills. Avoid inhalation of fumes or dust. Avoid contact with eyes, skin, and clothing. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Wear appropriate personal protective equipment when working with or handling. Always wash hands thoroughly after handling this product. Dispose of following Federal, State/Provincial, and Local regulations.

OTHER PRECAUTIONS: Empty containers may retain product residues in vapor, liquid, and/or solid form. All labeled hazard precautions should be observed.

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in work areas. Always wash hands after handling material and before applying or using cosmetics/food/drink/tobacco.

SECTION 7 NOTES: Keep out of reach of children. Not for internal consumption.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limit Values:

Also see section 3.

ENGINEERING CONTROLS: Use only with production equipment designed for use with tacky flux.

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLVs.

RESPIRATORY PROTECTION: A (US: NIOSH; EU: EN 140:1998, EN 14387:2004 A)-approved air-purifying respirator with fume/organic chemical cartridge should be worn when airborne concentrations may be exceeded. General and local exhaust ventilation is the preferred means of protection.

EYE PROTECTION: Use with appropriate eye protection: Goggles or face shield (EU: EN 166-S 3 9).

SKIN PROTECTION: Protective gloves should be worn when the possibility of skin contact exists (EU: EN 374-1:2003).

Stable NE

PROTECTIVE CLOTHING OR EQUIPMENT: Work clothes should be worn and laundered in accordance with current Lead (Pb) standards (US: OSHA).

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in areas where solder products may be used. Always wash hands after handling soldering products and before applying or using cosmetics/food/drink/tobacco.

OTHER: Maintain eye wash stations in work areas. Avoid the use of contact lenses in high fume areas. Clean protective equipment regularly. Clean up spills immediately.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: ODOR: ODOR THRESHOLD: pH as SUPPLIED: MELTING POINT: FREEZING POINT: INITIAL BOILING POINT: BOILING RANGE: FLASH POINT: EVAPORATION RATE: FLAMMABILITY (solid): UPPER/LOWER FLAMMABILITY: UPPER/LOWER FLAMMABILITY: UPPER/LOWER EXPLOSIVE LIMITS: VAPOR PRESSURE (mmHg): VAPOR DENSITY (AIR = 1): RELATIVE DENSITY: SOLUBILITY IN WATER: PARTITION COEFFICIENT (n-octanol/water): AUTOIGNITION TEMPERATURE: DECOMPOSITION TEMPERATURE: VISCOSITY:	Clear to Dark Amber liquid Sharp, irritating NE N/A NE 149°C (300°F) NE 82°C (180°F) NE NE NE NE NE NE NA NA N/A NA NA NA NA NA NA NA NA
10. STABILITY AND REACTIVITY	

STABILITY:	
CONDITIONS TO AVOID (STABILITY):	

11. TOXICOLOGICAL INFORMATION

INHALATION:

May cause respiratory irritation.

SKIN:

Causes skin irritation. Bonds skin in seconds.

EYES:

Causes serious eye irritation. Liquid product will bond eyelids.

ACUTE TOXICITY: SKIN CORRISION/IRRITATION: SERIOUS EYE DAMAGE/IRRITATIO RESPIRATORY OR SKIN SENSITIZ GERM CELL MUTAGENICITY:				
CARCINOGENICITY:	1			1
OSHA: N/A	ACGIH: N/A	NTP: N/A	IARC: N/A	
REPRODUCTIVE TOXICITY:	Not available			
STOT-SINGLE EXPOSURE:	NE			
STOT-REPEATED EXPOSURE:	NE			
ASPIRATION HAZARD:	NE			
12. ECOLOGICAL INFORMATIC	DN			
TOVICITY				

TOXICITY:	NE
PERSISTENCE AND DEGRADIBILITY:	NE
BIOACCUMULATIVE POTENTIAL:	NE
MOBILITY IN SOIL:	NE
RESULT OF PBT and vPvB ASSESSMENT:	Not applicable
OTHER ADVERSE EFFECTS:	NE

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Scrap and waste should be recycled or stored in a dry, sealed container for later disposal. Disposal must be in accordance with Federal, State/Provincial, and Local Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

UN Number: UN Proper Shipping Name: Packaging Group: Environmental Hazards:	Not available Not available Not applicable None
TRANSPORT HAZARD CLASSES:	
US DOT Hazardous Material Classification:	Non-Hazardous (≤ 450.000ml per shipment)
Water Transportation:	Non-Hazardous
IATA Hazardous Material Classification:	Non-Hazardous (≤ 1000ml per shipment, ≤ 30ml per inner package)
	Aviation Regulated Liquid, N.O.S. (Ethyl Cyanoacrylate). Class: 9. Packing Group: III. Marine
	Pollutant: No. (> 1000ml per shipment, > 30ml per inner package)
ADR Road Regulations	Not regulated
IMDG Sea Regulations	Not regulated
ADG Land Transportation	Not regulated

15. REGULATORY INFORMATION

All ingredients used to manufacture this product are listed on the EPA TSCA Inventory. Finished product is not listed on the EPA TSCA Inventory.

U.S. FEDERAL REGULATIONS:	Not regulated
STATE REGULATIONS:	Not regulated
INTERNATIONAL REGULATIONS:	Not regulated
AUSTRALIAN REGULATIONS:	Not regulated

16. OTHER INFORMATION

NE NE

Rapid exothermic polymerization will occur in the presence of water, amines and alcohols.

BCF	Bioconcentration factor
C.A.S.	Chemical Abstract Service
CLP	Classification, Labeling and Packaging
DOT	Department of Transportation
EC	Effective Concentration
EPA	Environmental Protection Agency
GHS	Global Harmonized System
HMIS	Hazardous Material Identification System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal Concentration
LD	Lethal Dose
NA	Not available
NE	Not established
NIOSH	National Institute for Occupational Safety & Health
NOEC	No observed effective concentration
NOHSC	National Occupational Health and Safety Commission (Australia)
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
Pow	Octanol water partition coefficient
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
STOT	Specific target organ toxicity
TLV	Threshold Limit Value
TSCA	Toxic Substance Control Act
TWA:	Time Weighted Average
US DOT:	United States Department of Transportation

PREPARATION INFORMATION:

This update supersedes all previously released documents.

DISCLAIMER:

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to Chip Quik at the time of issue. No warranty, guarantee, or representation is made by Chip Quik nor does Chip Quik assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances. The data on this Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet as a source for hazard information.

Copyright © 1994-2021 Chip Quik® Inc.