

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

1t1359is14#trpbf

(Engineering Calculation)

SOIC

(printed on: 2020-07-11 20:07:43)

**TOTAL MASS (g) : 0.134753**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.003703	1000000	27479.8164062		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000154	1000000	1142.82775879		
Lead Frame	A42	Copper (Cu)	7440-50-8	0.000000	0	0		
		Iron (Fe)	7439-89-6	0.025972	580000	192737.171875		
		Phosphorus (P)	7723-14-0	0.000000	0	0		
		Zinc (Zn)	7440-66-6	0.000000	0	0		
		Nickel (Ni)	7440-02-0	0.018808	420000	139573.421875		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.044780</b>	<b>1000000</b>	<b>332310.625</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.002585	1000000	19186.4296875		
		<b>External Plating Total:</b>				<b>0.002585</b>	<b>1000000</b>	<b>19186.4296875</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000358	1000000	2656.70361328		
<b>Internal Plating Total:</b>				<b>0.000358</b>	<b>1000000</b>	<b>2656.70361328</b>		
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.001048	750000	7777.16601562		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000349	250000	2589.9152832		
<b>Die Attach Total:</b>				<b>0.001397</b>	<b>1000000</b>	<b>10367.0810547</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.010585	130000	78550.859375		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.067581	830000	501515.9375		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.002850	35000	21149.7382812		
		Carbon Black (C)	1333-86-4	0.000407	5000	3020.33105469		
		<b>Encapsulation Total:</b>				<b>0.081423</b>	<b>1000000</b>	<b>604236.8125</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000353	1000000	2619.59887695		
					<b>TOTAL MASS (g) :</b>	<b>0.134753</b>		