# **GLOW FISH RODS** NON-CONDUCTIVE FIBERGLASS



7-36-231

## NON-CONDUCTIVE FIBERGLASS RODS FOR WIRING

With our proprietary luminescent resin, Jameson is the original manufacturer of fiberglass glow rods.

These non-conductive rods are perfect for attics, drop ceilings, floors, walls, and crawl spaces. Their high strength and flexibility will handle turns easily without breaking.

Designed for maximum versatility, threaded ferrules make it possible to customize rod length to any job and a variety of accessories make it easier to handle any wiring situation.

#### 1/4" DIAMETER GLOW RODS

Most Rigid Glow Rod; Used For Long Spans Minimum Bend Radius: 6" Tensile/Pull Strength: 750 lbs

Part Number	Total Rod Length	Package Length	1/4" Glow Rod Kits
7-36-23T	24'	6'	Three 6' X 1/4" Rods, Two 3' X 1/4" Rods. Includes One Bullet Nose with Eyelet, One Hook
7-63T	18'	3'	Six 3' X 1/4" Rods. Includes One Bullet Nose with Eyelet, and One Hook
7-34T	12'	4'	Three 4' X 1/4" Rods. Incudes One Bullet Nose with Eyelet, One Hook

### 3/16" DIAMETER GLOW RODS

More Flexible For Short Runs Or Use In Limited Space Minimum Bend Radius: 4" Tensile/Pull Strength: 500 lbs

Part Number	Total Rod Length	Package Length	3/16" Glow Rod Kits
7S-45T	20'	5'	Four 5' X 3/16" Rods. Includes One Bullet Nose with Eyelet, One Hook
7S-35T	15'	5'	Three 5' x 3/16" Rods. Includes One Bullet Nose with Eyelet, One Hook
7S-718T	10.5'	18"	Seven 18" X 3/16" Rods. Includes One Bullet Nose with Eyelet, One Hook



5/32" Rod

What Size Do You Need?

Flexibility Increases As Rod Diameter Decreases

- 1/4" for long spans requiring greater rigidity
- 3/16" for short spans or in limited space

800-346-1956 | JAMESONTOOLS.COM

5/32" for making tight turns

Using the same size ferrules (#8-32), different diameter rods can be used together in any combination for ultimate on-the-job customization.





7S-351

7S-718T

#### 5/32" DIAMETER GLOW RODS

Smallest Diameter Offers Extreme Flexibility With High Strength Minimum Bend Radius: 3.5" Tensile/Pull Strength: 300 lbs

Part Number	Total Rod Length	Package Length	1/4" Glow Rod Kits
7SS-36T	18'	6'	Three 6' X 5/32" Rods. Includes One Bullet Nose with Eyelet, One Hook
7SS-6	6'	*	One 6' X 5/32" Rod with Permanently Mounted Bullet Nose with Eyelet On Each End of Rod

\* Single rods shipped with hanging tag, not in clear plastic kit tube

#### COMBO GLOW ROD KITS

A Variety Of Rod Sizes And Accessories For Greater Versatility On The Job

Part Number	Total Rod Length	Package Length	Installer's Kit
7-8-IK	35'	6'	Two 1/4" X 5' Rods, Two 1/4" X 2.5' Rods, Four 3/16" X 5' Rods. Includes Two Bullet Nose with Eyelet, Two Hooks, One Whisk

Part Number	Total Rod Length	Package Length	Deluxe Kit
7S-65K	30'	6'	Six 3/16" X 5' Rods. Includes One Bullet Nose with Eyelet, One Hook, One Whisk, One Ball Chain Bullet Nose

Part Number	Total Rod Length	Package Length	Versa Kit
7-8VK	34'	6'	Two 1/4" X 6' Rods, Two 3/16" X 5' Rods, and One 5/32" X 6' Rod. Includes One 5/32" X 6' Rod Bullet Nose with Eyelet, One Hook, One Whisk, One Ball Chain Bullet Nose, One Hook, One Whisk

#### **GLOW ROD ACCESSORIES**

To Handle Any Wiring Job

Part Number	Glow Rod Accessories
7-00A	Bullet Nose with Eyelet
7-01A	Hook
7-02A	Bullet Nose with Ring
7-03A	Whisk
7-04A	Ball Chain Bullet Nose
7-05A	Magnet
7-06AK	Accessory Kit



Accessory Kit Hook Magnet

Whisk Ball Chain Bullet Nose with Ring Bullet Nose with Eyelet




Bullet Nose with Ring Pull line or grab with hook

Magnet

Hook

Retrieve Ball Chain

Grasp and retrieve



Whisk Guide rod; avoid obstacles



7SS-36T

7-8-IK

7S-65K

7-8VK

7SS-6

Permanently mounted bullet

nose on each end.

**Ball Chain Bullet Nose** Use with Magnet for retrieval

\*\*\*\*\*\*