

Product: <u>1829P</u> ⊠

Broadband Coax, Series 6, 18 AWG Solid BCCS, Foil + 60% AL Braid, Flamarrest® Jkt, CMP

Product Description

Broadband Coax, Series 6, 18 AWG Solid Bare Copper Covered Steel Conductor, FEP Insulation, Foil + 60% Aluminum Braid Shield, Flamarrest® Jacket, CMP

Technical Specifications

Product Overview

	broaubanu, Cab	e Television (CATV), RF drop	cable, Direct Br	oadcast Satellite (DBS), Over-The	-Air (OTA) antennas	
onstruction Details	5					
Series Type:	6					
onductor						
Size Stranding Nom	. Diameter	Material				
18 AWG Solid 0.04	0 in BCCS - Bare	e Copper Covered Steel				
nsulation						
Material	Nom	. Insulation Diameter				
FEP - Fluorinated Ethylene	Propylene (Foam) 0.170					
Duter Shield						
Layer Outer Shield Type	Material	Material Trade Nan	ne Coverage			
1 Tape	Tri-Laminate (Alum+Pol		100%			
2 Braid	Aluminum		60%			
Material PVC - Polyvinyl Chloride 0		m)				
	minal): 0.235 in (5.97 mi					
Overall Cable Diameter (No						
Overall Cable Diameter (No						
Overall Cable Diameter (No Electrical Character Return Loss (RL)	istics					
Overall Cable Diameter (No Electrical Character Return Loss (RL) Frequency Min. Str						
Overall Cable Diameter (No Electrical Character Return Loss (RL) Frequency Min. Str 5 - 2500 MHz 15 dB	istics					
Overall Cable Diameter (No Electrical Character Return Loss (RL) Frequency Min. Str 5 - 2500 MHz 15 dB 2500 - 3000 MHz 10 dB	istics					
Overall Cable Diameter (No Electrical Character Return Loss (RL) Frequency Min. Str 5 - 2500 MHz 15 dB 2500 - 3000 MHz 10 dB Electricals	uctural Return Loss					
Overall Cable Diameter (No Electrical Character Return Loss (RL) Frequency Min. Str 5 - 2500 MHz 15 dB 2500 - 3000 MHz 10 dB Electricals Nom. Conductor DCR	istics uctural Return Loss Nom. Outer Shield D	DCR Nom. Capacitance Co		Nom. Characteristic Impedance 75 Ohm	Nom. Velocity of Prop.	

300 V (CMP)

Mechanical Characteristics

Bend Radius

Installation Min.	
2.4 in	
Max. Pull Tension:	150 lbs (68 kg)
Bulk Cable Weight:	25 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	NFPA 262
NEC / UL Compliance:	CMP, CATVP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	1829A

History

Update and Revision:

Revision Number: 0.369 Revision Date: 11-09-2022

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
1829P 010100	Black	Reel	100 ft	612825124078
1829P 010U250	Black	UnReel	250 ft	612825124054
1829P 010U500	Black	UnReel	500 ft	612825124061
1829P 010U1000	Black	UnReel	1,000 ft	612825124047
1829P 877100	Natural	Reel	100 ft	612825124115
1829P 877U250	Natural	UnReel	250 ft	612825124092
1829P 877U500	Natural	UnReel	500 ft	612825124108
1829P 8771000	Natural	Reel	1,000 ft	612825124122
1829P 877U1000	Natural	UnReel	1,000 ft	612825124085

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.