

# **Product:** <u>5100UP</u> ☑

Audio Cable, 2 Conductor 14 AWG, BC, Unshielded, CL3

# **Product Description**

Commercial Audio Cable, Rated-CL3, 2-14 AWG highly flexible stranded bare copper conductors with PVC insulation, PVC jacket with ripcord

# **Technical Specifications**

### Product Overview

Suitable Applic	cations:	Security S	ystem, Interco	om/PA, Audio/Speal	ker, Pov	ver-Limited Controls
Constructio	on Details					
onductor						
Element	Number of Ele	ement Size	Stranding	Material		
Conductor(s)	2	14 AWG	42x30	BC - Bare Copper		
sulation						
Element	Materia	al Non	n. Thickness	Color Code		
Conductor(s)	PVC - Polyviny	l Chloride 0.020	) in (0.51 mm)	Black, White		
Duter Jacket						
Materi	al No	m. Thickness	Nom. Diam	eter Ripcord		
PVC - Polyviny	/I Chloride 0.0	18 in (0.46 mm)	0.266 in (6.76	δ mm) Yes		
Overall Cable	Diameter (Nomi	inal): 0.266 in (6	6.76 mm)			
lectrical C	haracteris	tics				
lectricals			Nom Can	acitance Cond-to-	Cond	May Current
Electricals	Nom. Con	tics ductor DCR Oft (7.94 Ohm/km		acitance Cond-to-t		Max. Current 22 Amps per conductor @ 25°
Electricals Element Conductor(s)	Nom. Con	ductor DCR				
Electricals Element Conductor(s) /oltage	Nom. Con 2.42 Ohm/100(	ductor DCR				
Electricals Element Conductor(s) /oltage UL Voltage Ra	Nom. Con 2.42 Ohm/100(	ductor DCR				
Electricals Element Conductor(s) Voltage UL Voltage Ra 300 V (CL3)	Nom. Con 2.42 Ohm/1000	nductor DCR Dft (7.94 Ohm/km				
Electricals Element Conductor(s) /oltage UL Voltage Ra 300 V (CL3)	Nom. Con 2.42 Ohm/100(	nductor DCR Dft (7.94 Ohm/km				
Electricals Element Conductor(s) /oltage UL Voltage Ra 300 V (CL3)	Nom. Con 2.42 Ohm/1000	nductor DCR Dft (7.94 Ohm/km				
Electricals Element Conductor(s) Voltage UL Voltage Ra 300 V (CL3) Mechanica Temperature UL Temperature	Nom. Con 2.42 Ohm/1000 ating I Character	iductor DCR Dft (7.94 Ohm/km				
Electricals Element Conductor(s) Voltage UL Voltage Ra 300 V (CL3) Mechanica Temperature UL Temperature	Nom. Con 2.42 Ohm/1000 ating	iductor DCR Dft (7.94 Ohm/km				
Electricals Element Conductor(s) /oltage UL Voltage Ra 300 V (CL3) Vechanica	Nom. Con 2.42 Ohm/1000 ating I Character	iductor DCR Dft (7.94 Ohm/km				
Electricals Element Conductor(s) Voltage UL Voltage Ra 300 V (CL3) Vechanica Temperature UL Temperature UL Temperature Stationary Mil	Nom. Con 2.42 Ohm/1000 ating I Character -20°C to +1 n. Installation	istics				
Electricals Element Conductor(s) Voltage UL Voltage Ra 300 V (CL3) Vechanica Temperature UL Temperature UL Temperature Stationary Mil	Nom. Con 2.42 Ohm/1000 ating I Character -20°C to +1 n. Installation	istics				
Electricals Element Conductor(s) Voltage UL Voltage Ra 300 V (CL3) Mechanica Temperature UL Temperature 75°C	Nom. Con 2.42 Ohm/1000 ating I Character I Character -20°C to +1 n. Installation 2.7 in (69 m	istics Min. m) 109 lbs (4:	) 29 pF/ft (95	5 pF/m)		

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Flammability / Reaction to Fire:	UL1685 (UL Loading), IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, CL3
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

### History

Update and Revision:

Revision Number: 0.335 Revision Date: 12-19-2022

#### **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC
5100UP 010500	Black	Reel	500 ft	612825156529
5100UP 010U500	Black	UnReel	500 ft	612825433484
5100UP 0101000	Black	Reel	1,000 ft	612825156550
5100UP 010U1000	Black	UnReel	1,000 ft	612825156536
5100UP 010Z1000	Black	ReelTuff Box	1,000 ft	612825156611
5100UP 008U500	Gray	UnReel	500 ft	612825156505
5100UP 0081000	Gray	Reel	1,000 ft	612825156451
5100UP 008U1000	Gray	UnReel	1,000 ft	612825156468
5100UP 005500	Green, Dark	Reel	500 ft	612825156413
5100UP 005U500	Green, Dark	UnReel	500 ft	612825156475
5100UP 0051000	Green, Dark	Reel	1,000 ft	612825156444
5100UP 005U1000	Green, Dark	UnReel	1,000 ft	612825156420
5100UP 009500	White	Reel	500 ft	612825156482
5100UP 009U500	White	UnReel	500 ft	612825156543
5100UP 0091000	White	Reel	1,000 ft	612825156512
5100UP 009U1000	White	UnReel	1,000 ft	612825156499

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.