



# Product: <u>5500UE</u> ☑

Security & Sound, #22-2c BC, CMR

# **Product Description**

Security & Commercial Audio Cable, Riser-CMR, 2-22 AWG stranded bare copper conductors with polypropylene insulation, PVC jacket with ripcord

## **Technical Specifications**

## Product Overview

| 0  |                     | 0 11 0 1                       |   |                               |  |  |  |  |
|--|---------------------|--------------------------------|---|-------------------------------|--|--|--|--|
| Suitable Appli   | cations:            | Security Systems,              | ecurity Systems, Intercom/PA Systems, Sound/Audio Systems, Power Limited Controls, Single Line Telephor |                               |  |  |  |  |
| constructi   | on Details          |                                |   |                               |  |  |  |  |
| Conductor  |                     |                                |   |                               |  |  |  |  |
| Element  | Number of Element   | Size Strand                    | ding Material   |                               |  |  |  |  |
| Conductor(s)   |                     | 22 AWG 7x30                    | BC - Bare Copper  |                               |  |  |  |  |
| nsulation  |                     |                                | 1   |                               |  |  |  |  |
| Element  | Material            | Nom. Thickness                 | Nom. Insulation Diameter  | Color Code                    |  |  |  |  |
| Conductor(s)   | PP - Polypropylene  |                                |   | Black, Red                    |  |  |  |  |
|  |                     |                                |   |                               |  |  |  |  |
| Outer Jacket   |                     |                                |   |                               |  |  |  |  |
| Material Nom. Thickness Nom. Diameter Ripcord   PVC - Polyvinyl Chloride 0.017 in (0.43 mm) 0.123 in (3.12 mm) Yes |                     |                                |   |                               |  |  |  |  |
|  |                     |                                | , ,   |                               |  |  |  |  |
| Overall Cable  | Diameter (Nominal): | 0.123 in (3.12 mm)             | )   |                               |  |  |  |  |
| Electrical (   | Characteristics     |                                |   |                               |  |  |  |  |
|  |                     |                                |   |                               |  |  |  |  |
| Electricals<br>Element   | Nom. Conducto       | or DCR Nom                     | . Capacitance Cond-to-Con   | d Max. Current                |  |  |  |  |
| Conductor(s)   |                     | 2.8 Ohm/km) 17 pF/ft (56 pF/m) |   | 2.8 Amps per conductor @ 25°C |  |  |  |  |
| .,   |                     | , ,                            | 、 · · /   |                               |  |  |  |  |
| /oltage  |                     |                                |   |                               |  |  |  |  |
| UL Voltage R   | ating               |                                |   |                               |  |  |  |  |
| 300 V (CMR)  |                     |                                |   |                               |  |  |  |  |
| Mechanica  | I Characteristic    | S                              |   |                               |  |  |  |  |
| <b></b>  |                     |                                |   |                               |  |  |  |  |
| Femperature<br>UL Temperat   | ure Operating       |                                |   |                               |  |  |  |  |
| 75°C   | -20°C to +75°C      |                                |   |                               |  |  |  |  |
|  |                     |                                |   |                               |  |  |  |  |
| Bend Radius  |                     | 1                              |   |                               |  |  |  |  |
| Stationary Mi  |                     |                                |   |                               |  |  |  |  |
| 1.2 in (30 mm  | , , ,               |                                |   |                               |  |  |  |  |
| Max. Pull Ten  |                     | 18 lbs (8.2 kg)                |   |                               |  |  |  |  |
| Bulk Cable Weight: 8 lbs/1000ft (12 kg/km)   |                     |                                |   |                               |  |  |  |  |
|  | and Complianc       |                                |   |                               |  |  |  |  |

| Environmental Suitability:       | Indoor - Riser, Indoor   |  |  |  |  |
|----------------------------------|--|--|--|--|--|
| Flammability / Reaction to Fire: | UL1666 Riser, IEEE 1202 FT4, IEC 60332-1-2                                   |  |  |  |  |
| CPR Compliance:                  | CPR Euroclass: Eca   |  |  |  |  |
| NEC / UL Compliance:             | Article 800, CMR   |  |  |  |  |
| CEC / C(UL) Compliance:          | CMG  |  |  |  |  |
| European Directive Compliance:   | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |  |  |  |  |
| UK Regulation Compliance:        | UKCA Mark  |  |  |  |  |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)  |  |  |  |  |
| Plenum Number:                   | 6500UH   |  |  |  |  |

# History

Update and Revision:

Revision Number: 0.357 Revision Date: 01-04-2023

#### **Part Numbers**

#### Variants

| Item #          | Color       | Putup Type   | Length   | UPC/EAN       |
|-----------------|-------------|--------------|----------|---------------|
| 5500UE.00152    | Chrome      | Reel         | 152 m    | 8719605008596 |
| 5500UE.00305    | Chrome      | Reel         | 305 m    | 8719605008602 |
| 5500UE 008500   | Gray        | Reel         | 500 ft   | 612825162896  |
| 5500UE 008U500  | Gray        | UnReel       | 500 ft   | 612825420033  |
| 5500UE 0081000  | Gray        | Reel         | 1,000 ft | 612825162919  |
| 5500UE 008U1000 | Gray        | UnReel       | 1,000 ft | 612825162902  |
| 5500UE 008Z1000 | Gray        | ReelTuff Box | 1,000 ft | 612825163145  |
| 5500UE 005Z1000 | Green       | ReelTuff Box | 1,000 ft | 612825337171  |
| 5500UE 005U1000 | Green, Dark | UnReel       | 1,000 ft | 612825420026  |

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.