



# Product: <u>6502GE</u> ☑

Security & Sound, #22-2c, BC, Shielded, CMP

# **Product Description**

Security & Sound Cable, Plenum-CMP, 1-22 AWG stranded bare copper pair with Flamarrest® insulation and Beldfoil® shield, 2-22 AWG stranded bare copper conductors with insulation, overall Flamarrest® jacket with ripcord

# **Technical Specifications**

# **Product Overview**

Suitable Applications:

Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy Environment

# **Construction Details**

#### Conductor

Element	Number of Element	Size	Stranding	Material
Pair(s)	1	22	7x30	BC - Bare Copper
Conductor(s)	2	22	7x30	BC - Bare Copper

### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	PVC - Polyvinyl Chloride	0.009 in (0.23 mm)	0.047 in (1.2 mm)	Black & Red
Conductor(s)	PVC - Polyvinyl Chloride	0.009 in (0.23 mm)	0.047 in (1.2 mm)	White, Green

#### Inner Shield

Element	Shield Type	Material	Coverage	Drainwire Type
Each Pair	Таре	Bi-Laminate (Alum+Poly)	100%	16 AWG (7x24) TC
Conductor(s)	No Shield			

# Outer Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.015 in (0.38 mm)	0.155 in (3.94 mm)	Yes

# **Electrical Characteristics**

#### Electricals

Element	Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Pair(s)	17.24 Ohm/1000ft	3.23 Ohm/1000ft (10.6 Ohm/km)	55 pF/ft (180 pF/m)	99 pF/ft (320 pF/m)	2.2 Amps per Conductor at 25°C
Conductor(s)	17.2 Ohm/1000ft (56.4 Ohm/km)				

# Voltage

UL Voltage Rating 300 V

# **Mechanical Characteristics**

_	
Tem	perature

UL Temperature 75°C

#### Bend Radius

 Stationary Min.
 Installation Min.

 1.55 in (39.4 mm)
 1.55 in (39.4 mm)

 Max. Pull Tension:
 36.4 lbs (16.5 kg)

 Bulk Cable Weight:
 19 lbs/1000ft

**Standards and Compliance** 

Environmental Suitability:	Outdoor
Flammability / Reaction to Fire:	NFPA 262 (UL910), FT6
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	5502GE

# **History**

Update and Revision:

Revision Number: 0.430 Revision Date: 01-20-2023

# Part Numbers

#### Variants UPC Colo 6502GE 010C100 Black 612825177661 6502GE 010U1000 Black 612825177678 6502GE 008U1000 Gray 612825177623 6502GE 8771000 Natural 612825177708 6502GE 877U1000 Natural 612825177692 6502GE 009C100 White 612825177630 6502GE 009U1000 White 612825177647

### © 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.