

| Product: <u>83004</u> ☑ | |
|-----------------------------|---------------|
| Lead Wire, #24 Str SPC, TFE | Ins, AWM 1213 |
| 😭 Request Sample | |

Product Description

High Temp Plastic Lead Wire, 24AWG (7x32) Silver Plated Copper, TFE Insulation, AWM 1213 105C TYPE E MIL-W-16878/4 600V 200C

Technical Specifications

Product Overview

| Suitable Appli | Suitable Applications: high temperature, inter-connection circuits, internal wiring of computer and electronic equipments, (Type E) MIL-W-1687 | | | | nal wiring of computer and electronic equipments, (Type E) MIL-W-16878/4 applicat |
|--|--|--------|-----------|----------------------|---|
| Construction Details | | | | | |
| Conductor | | | | | |
| Element | Number of Elemen | t Size | Stranding | Material | |
| Conductor(s) | | 24 AWG | | SC - Silvered Copper | |
| Insulation | | | | | |
| Material Nom. Thickness Nom. Insulation Diameter | | | | | |
| PTFE - Polytetrafluoroethylene 0.01 in (0.25 mm) 0.044 in (1.1 mm) | | | | | |
| Overall Cable Diameter (Nominal): 0.044 in (1.1 mm) | | | | | |
| Electrical Characteristics | | | | | |
| | | | | | |
| Electricals | | | | | |
| Nom. Conductor DCR Max. Current | | | | | |
| 24 Ohm/1000ft Mil-Std-975M Table 3.16 (single wire): 10 A | | | | | |

Voltage

UL Voltage Rating 600 V RMS

Mechanical Characteristics

| emperature | |
|-----------------------|---------------|
| JL Temperature | Operating |
| 200°C -70 | 0°C To +200°C |
| end Radius | |
| Stationary Min. Insta | allation Min. |
| 0.44 in (11 mm) 0.44 | in (11 mm) |
| Max. Pull Tension: | ł |
| Bulk Cable Weight: | |

Standards and Compliance

| Environmental Suitability: | Indoor, Outdoor |
|----------------------------------|-----------------|
| Sustainability: | CA Prop 65 |
| Flammability / Reaction to Fire: | VW-1 |
| AWM Compliance: | AWM 1213 |

| NEMA Compliance: | HP3 |
|--------------------------------|---|
| Military Compliance: | MIL-W-16878/4 |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| History | |

Update and Revision:

Revision Number: 0.482 Revision Date: 01-20-2023

Part Numbers

Variants Putup Type Length UPC Item # Color 83004 010100 Black Reel 100 ft 83004 0101000 Black Reel 1.000 ft 612825354406 83004 006100 100 ft 612825354383 Blue, Liaht Reel 83004 0061000 Blue, Light Reel 1,000 ft 612825354314 83004 001100 100 ft Brown Reel 83004 0011000 Brown 1,000 ft 612825399292 Reel 83004 008100 100 ft 612825354390 Grav Reel 83004 0081000 Gray Reel 1,000 ft 83004 005100 100 ft Green Dark Reel 83004 0051000 Green, Dark Reel 1,000 ft 612825354307 83004 003100 Orange Reel 100 ft 612825354376 83004 0031000 Orange 1,000 ft 612825399308 Reel 83004 002100 Red Reel 100 ft 83004 0021000 Red 1,000 ft 612825354321 Reel 83004 007100 Violet Reel 100 ft 83004 0071000 Violet 1.000 ft Reel 83004 009100 White 100 ft Reel 83004 0091000 White Reel 1.000 ft 612825378341 83004 004100 Yellow Reel 100 ft 83004 0041000 Yellow 1.000 ft 612825354369 Reel

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.