



**Product:** <u>83005</u> ☑

Lead Wire, #22 Str SPC, TFE Ins, AWM 1213

Request Sample

# **Product Description**

High Temp Plastic Lead Wire, 22AWG (7x30) Silver Plated Copper, TFE Insulation, AWM 1213 105C TYPE E MIL-W-16878/4 600V 200C

# **Technical Specifications**

### **Product Overview**

Suitable Applications: high temperature, inter-connection circuits, internal wiring of computer and electronic equipments, (Type E) MIL-W-16878/4 applications

### **Construction Details**

#### Conductor

	Element	Number of Element	Size	Stranding	Material
ľ	Conductor(s)	1	22 AWG	7x30	SC - Silvered Copper

#### Insulation

	Material	Nom. Thickness	Nom. Insulation Diameter
	PTFE - Polytetrafluoroethylene	0.01 in (0.25 mm)	0.050 in (1.3 mm)
ı	Overall Cable Diameter (Nomin	al). 0.05 in (1.3 mm	1)

### **Electrical Characteristics**

#### Electricals

Nom. Conductor DCR	Max. Current		
15.25 Ohm/1000ft	Mil-Std-975M Table 3.16 (single wire): 4.5 amps		

### Voltage

UL Voltage Rating 600 V RMS

# **Mechanical Characteristics**

### Temperature

<b>UL Temperature</b>	Operating		
200°C	-70°C To +200°C		

### Bend Radius

Stationary win.	installation win.
0.5 in (13 mm)	0.5 in (13 mm)
Max. Pull Tensio	n:
Bulk Cable Weig	ht:

## **Standards and Compliance**

Environmental Suitability:	Indoor, Outdoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	VW-1
AWM Compliance:	AWM 1213

NEMA Compliance:	HP3	
Military Compliance:	MIL-W-16878/4	
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	

### **History**

Update and Revision:	Revision Number: 0.481 Revision Date: 01-20-2023

### **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC
83005 010100	Black	Reel	100 ft	612825354161
83005 0101000	Black	Reel	1,000 ft	612825353683
83005 006100	Blue, Light	Reel	100 ft	
83005 0061000	Blue, Light	Reel	1,000 ft	612825354123
83005 001100	Brown	Reel	100 ft	
83005 0011000	Brown	Reel	1,000 ft	612825399315
83005 008100	Gray	Reel	100 ft	
83005 0081000	Gray	Reel	1,000 ft	
83005 005100	Green, Dark	Reel	100 ft	
83005 0051000	Green, Dark	Reel	1,000 ft	
83005 003100	Orange	Reel	100 ft	
83005 0031000	Orange	Reel	1,000 ft	
83005 002100	Red	Reel	100 ft	612825354352
83005 0021000	Red	Reel	1,000 ft	612825354345
83005 007100	Violet	Reel	100 ft	
83005 0071000	Violet	Reel	1,000 ft	
83005 009100	White	Reel	100 ft	612825354338
83005 0091000	White	Reel	1,000 ft	612825354130
83005 004100	Yellow	Reel	100 ft	
83005 0041000	Yellow	Reel	1,000 ft	612825354147

### © 2023 Belden, Inc

### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.