



Product: <u>8457</u> ☑

Electronic, 12 C #22 Str TC, PVC Ins, PVC Jkt, CMG

Request Sample

Product Description

Electronic, 12 Conductor 22AWG (7x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

Technical Specifications

Product Overview

Suitable Applications: low voltage analog signals (4-20ma, 0-10v,); low voltage control (24v,); line level audio; voice communication					voltage control (24v,); line level audio; voice communications; panel wiring	
Construction Details						
Sonductor						
Element	Number of Element	Size	Stranding	Material		
Conductor(s)	12	22 AWG	7x30	TC - Tinned Copper		
insulation						
Element	Material	Nom	. Thickness	Nom. Insulation Diame	r Color Code	
Conductor(s)	PVC - Polyvinyl Chloride	0.011	in (0.28 mm)	0.050 in (1.3 mm)	White, Black, Blue, Brown, Green, Gray, Orange, Purple, Red, Pink, Tan, Yell	

Outer Jacket

	Material	Nom. Thickness	Nom. Diameter	
PVC	C - Polyvinyl Chloride	0.032 in (0.81 mm)	0.272 in (6.91 mm)	
Ove	Overall Cable Diameter (Nominal): 0.272 in (6.91 mm)			

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current	
Conductor(s)	18 Ohm/1000ft	34 pF/ft (110 pF/m)	4.2 Amps per Conductor at 30°C	

Voltage

UL Voltage Rating
150 V (CMG), 150 V (UL AWM 2576)

Mechanical Characteristics

UL Temperature	Operating
80°C	-20°C to +80°C
Bend Radius	
Stationary Min.	Installation Min.
2.7 in (69 mm)	2.7 in (69 mm)
Max. Pull Tension	:
Bulk Cable Weight:	

Environmental Suitability:	Indoor			
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, FT4, IEC 60332-1-2			
CPR Compliance:	CPR Euroclass: Eca			
NEC / UL Compliance:	Article 800, CMG			
AWM Compliance:	AWM 2576			
CEC / C(UL) Compliance:	CMG			
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)			
UK Regulation Compliance:	UKCA Mark			
APAC Compliance:	China RoHS II (GB/T 26572-2011)			

History

Update and Revision:

Revision Number: 0.511 Revision Date: 01-20-2023

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC
8457 060100	Chrome	Reel	100 ft	612825207993
8457 060500	Chrome	Reel	500 ft	612825208013
8457 060U500	Chrome	UnReel	500 ft	612825207986
8457 0601000	Chrome	Reel	1,000 ft	612825208006
8457 060U1000	Chrome	UnReel	1,000 ft	612825207979
8457 0605000	Chrome	Reel	5,000 ft	612825208020

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.