



Product: <u>8718</u>

Electronic, 2 C #12 Str TC, PE Ins, OS, PVC Jkt, CL2

😭 Request Sample

Product Description

Electronic, 2 Conductor 12AWG (19x25) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CL2

Technical Specifications

Product Overview

Suitable	e Applications:		up t	to 600V analog signals ;
Const	ruction Details			
Conduc	tor			
	nt Number of Elem	ent Size	Stranding	Material
Pair(s)	1	12 AWG	19x25	TC - Tinned Copper
Insulatio	on			
Elemen	nt Material	Nom. Thic	kness No	m. Insulation Diamete
Pair(s)	PE - Polyethylene	0.037 in (0.	94 mm) 0.10	64 in (4.17 mm)
Outer S	hield			
Shield Type Material Coverage Drainwire Type				
Tape	Bi-Laminate (Alum+Poly)	100% 1	14 AWG (19x26) TC
Outer Ja	acket			
Material Nom. Thickness Nom. Diameter				
PVC - Polyvinyl Chloride 0.034 in (0.86 mm) 0.400 in (10.2 mm)				
Overall	Cable Diameter (Nor	ninal):	0.40	00 in (10.2 mm)

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Max. Current
Conductor(s)	1.78 Ohm/1000ft	25 pF/ft (82 pF/m)	49 pF/ft (160 pF/m)	55 Ohm	30 Amps per Conductor at 30°C

Voltage

UL Voltage Rating 600 V (UL AWM 20253), 300 V (CSA AWM)

Mechanical Characteristics

Temperature				
UL Temperature	Operating			
80°C	-20°C to +80°C			

Bend Radius

Stationary Min.Installation Min.4.0 in (100 mm)4.0 in (100 mm)

Max. Pull Tension:	200 lbs (91 kg)
Bulk Cable Weight:	87 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL 1685 UL loading , FT1, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, CL2
AWM Compliance:	AWM 20253
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:

Revision Number: 0.529 Revision Date: 01-20-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
8718 060500	Chrome	Reel	500 ft	612825214212
8718 060U500	Chrome	UnReel	500 ft	612825214182
8718 0601000	Chrome	Reel	1,000 ft	612825214199
8718 0602000	Chrome	Reel	2,000 ft	612825214205
8718 0605000	Chrome	Reel	5,000 ft	612825214229

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.